SIEMENS

## Data sheet for SIMOTICS S-1FK7

**Article No. :** **1FK7064-4CH71-1RG2**



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

| Engineering data | |
|---|---|
| Rated speed (100 K) | 4,500 rpm |
| Number of poles | 6 |
| Rated torque (100 K) | 5.0 Nm |
| Rated current | 7.0 A |
| Static torque (60 K) | 10.00 Nm |
| Static torque (100 K) | 12.00 Nm |
| Stall current (60 K) | 12.20 A |
| Stall current (100 K) | 15.00 A |
| Moment of inertia | 7.500 kgcm² |
| Efficiency | 93.0 % |

| Physical constants | |
|---|---|
| Torque constant | 0.80 Nm/A |
| Voltage constant at 20° C | 50.5 V/1000*min⁻¹ |
| Winding resistance at 20° C | 0.17 Ω |
| Rotating field inductance | 6.2 mH |
| Electrical time constant | 36.50 ms |
| Mechanical time constant | 0.60 ms |
| Thermal time constant | 55 min |
| Shaft torsional stiffness | 29,500 Nm/rad |
| Net weight of the motor | 15.4 kg |

| Mechanical data | |
|---|---|
| Motor type | Permanent-magnet synchronous motor |
| Motor type | High Dynamic |
| Shaft height | 63 |
| Cooling | Natural cooling |
| Radial runout tolerance | 0.040 mm |
| Concentricity tolerance | 0.10 mm |
| Axial runout tolerance | 0.10 mm |
| Vibration severity grade | Grade A |
| Connector size | M23 |
| Degree of protection | IP65 and DE flange IP67 |
| Design acc. to Code I | IM B5 (IM V1, IM V3) |
| Temperature monitoring | Pt1000 temperature sensor |
| Electrical connectors | Connectors for signals and power rotatable |
| Color of the housing | Standard (Anthracite RAL 7016) |
| Holding brake | without holding brake |
| Shaft end | Plain shaft |
| Encoder system | Encoder AM20DQI: absolute encoder 20 bits (resolution 1048576, encoder-internal 512 S/R) + 12 bits multi-turn (traversing range 4096 revolutions) |

| Optimum operating point | |
|---|---|
| Optimum speed | 3,500 rpm |
| Optimum power | 2.8 kW |

| Limiting data | |
|---|---|
| Max. permissible speed (mech.) | 7,500 rpm |
| Max. permissible speed (inverter) | 7,500 rpm |
| Maximum torque | 32.0 Nm |
| Maximum current | 46.0 A |

| Recommended Motor Module | |
|---|---|
| Rated inverter current | 18 A |
| Maximum inverter current | 54 A |
| Maximum torque | 32.00 Nm |