SIEMENS

## Data sheet for SIMOTICS S-1FK7

**Article No. :** **1FK7085-4CF71-1DA0**



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

| Engineering data | |
|---|---|
| Rated speed (100 K) | 3,000 rpm |
| Number of poles | 8 |
| Rated torque (100 K) | 6.5 Nm |
| Rated current | 7.0 A |
| Static torque (60 K) | 18.30 Nm |
| Static torque (100 K) | 22.00 Nm |
| Stall current (60 K) | 17.80 A |
| Stall current (100 K) | 22.00 A |
| Moment of inertia | 22.000 kgcm² |
| Efficiency | 92.0 % |

| Physical constants | |
|---|---|
| Torque constant | 1.00 Nm/A |
| Voltage constant at 20° C | 64.5 V/1000*min⁻¹ |
| Winding resistance at 20° C | 0.12 Ω |
| Rotating field inductance | 3.7 mH |
| Electrical time constant | 31.50 ms |
| Mechanical time constant | 0.78 ms |
| Thermal time constant | 65 min |
| Shaft torsional stiffness | 84,000 Nm/rad |
| Net weight of the motor | 23.0 kg |

| Mechanical data | |
|---|---|
| Motor type | Permanent-magnet synchronous motor |
| Motor type | High Dynamic |
| Shaft height | 80 |
| Cooling | Natural cooling |
| Radial runout tolerance | 0.050 mm |
| Concentricity tolerance | 0.10 mm |
| Axial runout tolerance | 0.10 mm |
| Vibration severity grade | Grade A |
| Connector size | M40 |
| Degree of protection | IP64 |
| Design acc. to Code I | IM B5 (IM V1, IM V3) |
| Temperature monitoring | Pt1000 temperature sensor |
| Electrical connectors | Connectors for signals and power rotatable |
| Color of the housing | Standard (Anthracite RAL 7016) |
| Holding brake | without holding brake |
| Shaft end | Feather key |
| Encoder system | Encoder IC22DQ: incremental encoder 22 bits (resolution 4194304, encoder-internal 2048 S/R) + commutation position 11 bits |

| Optimum operating point | |
|---|---|
| Optimum speed | 2,500 rpm |
| Optimum power | 3.1 kW |

| Limiting data | |
|---|---|
| Max. permissible speed (mech.) | 6,000 rpm |
| Max. permissible speed (inverter) | 6,000 rpm |
| Maximum torque | 65.0 Nm |
| Maximum current | 84.0 A |

| Recommended Motor Module | |
|---|---|
| Rated inverter current | 30 A |
| Maximum inverter current | 72 A |
| Maximum torque | 59.80 Nm |