SIEMENS

Data sheet 6AG1134-4LB02-2AB0



Figure similar

SIPLUS ET 200S EM 2AI HF based on 6ES7134-4LB02-0AB0 with conformal coating, -25…+60 °C, 2 AI U High Feature for ET 200S, 15 mm width, cycle time per module: 0.5 ms, +/-10 V; 15 bit+sign, +/-5 V; 15 bit+sign, 1..5 V; 15 bit, operational limit +/-0.1% with SF LED (group fault)

General information	
Product function	
● Isochronous mode	Yes
Supply voltage	
Load voltage L+	
● Rated value (DC)	24 V
● Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	55 mA
from backplane bus 3.3 V DC, max.	10 mA
Output voltage	
Power supply to the transmitters	
● present	No
Power loss	
Power loss, typ.	0.85 W
Address area	
Address space per module	
● Address space per module, max.	4 byte
Analog inputs	
Number of analog inputs	2
permissible input voltage for voltage input (destruction limit), max.	35 V; 35 V continuous; 75 V for max. 1 ms
Cycle time (all channels) max.	0.5 ms; 0.5 ms for 2 channels without noise suppression, 18 / 21 ms per channel with noise suppression
Input ranges (rated values), voltages	
● 1 V to 5 V	Yes
— Input resistance (1 V to 5 V)	800 kΩ
● -10 V to +10 V	Yes
— Input resistance (-10 V to +10 V)	800 kΩ
● -5 V to +5 V	Yes
— Input resistance (-5 V to +5 V)	800 kΩ
Cable length	
● shielded, max.	200 m
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
● Resolution with overrange (bit including sign), max.	16 bit; 0 to 5 V: 15 bit, ±10 V: 16 bit, ±5 V: 16 bit
● Integration time, parameterizable	Yes
● Interference voltage suppression for interference frequency f1 in Hz	60 / 50 Hz / no

© Copyright Siemes

● Conversion time (per channel)	0.04 ms; Without noise suppression 17/20 ms per channel with error
Smoothing of measured values	
● parameterizable	Yes; In 4 stages: 1x, 4x, 16x, 32x cycle time
● Step: None	Yes; 1x
● Step: low	Yes; 4x
● Step: Medium	Yes; 16x
● Step: High	Yes; 32x
Encoder	
Connection of signal encoders	
● for voltage measurement	Yes
Errors/accuracies	
Operational error limit in overall temperature range	
● Voltage, relative to input range, (+/-)	0.15 %; 0,25 % without interference frequency suppression
Basic error limit (operational limit at 25 °C)	
● Voltage, relative to input range, (+/-)	0.05 %; 0.1% without interference frequency suppression
Interrupts/diagnostics/status information	
Alarms	
● Hardware interrupt	Yes
Diagnoses	
● Wire break	Yes; Measuring range 1 to 5 V only
● Group error	Yes
● Overflow/Underflow	Yes
Diagnostics indication LED	
● Group error SF (red)	Yes
Potential separation	
Potential separation analog inputs	
● between the channels	No; however, increased permissible potential difference between the inputs.
● between the channels and backplane bus	Yes
● Between the channels and load voltage L+	Yes
Isolation	
Isolation tested with	500 V DC
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Ambient temperature during operation	
● min.	-25 °C; = Tmin
● max.	60 °C; = Tmax
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	5 000 m
● Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
● With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost permitted (no commissioning in bedewed state)
Resistance	
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	

© Copyright Siemes

— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!

Dimensions

Width	15 mm
Height	81 mm
Depth	52 mm

Weights

Weight, approx.	45 g

Classifications

	Version	Classification
eClass	16	27-24-26-01
eClass	14	27-24-26-01
eClass	12	27-24-26-01
eClass	9.1	27-24-26-01
eClass	9	27-24-26-01
eClass	8	27-24-26-01
eClass	7.1	27-24-26-01
eClass	6	27-24-26-01
ETIM	10	EC001596
ETIM	9	EC001596
ETIM	8	EC001596
ETIM	7	EC001596
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Manufacturer Declaration

China RoHS

Metrological Approval

General Product Approval	EMV	For use in hazardous locations

CCC-Ex

last modified: 5/13/2024

© Copyright Siemens