SIEMENS

Data sheet 6AG1134-6GF00-7AA1



Figure similar

SIPLUS ET 200SP AI 8xI 2-/4-wire BA based on 6ES7134-6GF00-0AA1 with conformal coating, -40…+70 °C, analog input module, suitable for BU type A0, A1, color code CC01, module diagnostics, 16 bit

General information	
Product type designation	AI 8xI 2-/4-wire BA
Firmware version	
● FW update possible	Yes
based on	6ES7134-6GF00-0AA1
usable BaseUnits	BU type A0, A1
Color code for module-specific color-coded label	CC01
Product function	
● I&M data	Yes; I&M0 to I&M3
● Isochronous mode	No
● Measuring range scalable	No
Engineering with	
● STEP 7 TIA Portal configurable/integrated from version	see entry ID: 109746275
Operating mode	
● Oversampling	No
● MSI	No
CiR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Calibration possible in RUN	No
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption (rated value)	25 mA; rated voltage, all channels active, no load
Current consumption, max.	725 mA; worst case voltage, all channels active, max. load, no derating
Encoder supply	
24 V encoder supply	
● 24 V	Yes
● Short-circuit protection	Yes
● Output current, max.	0.7 A; total current of all encoders/channels
Power loss	
Power loss, typ.	0.7 W; rated voltage, 50 % active channels, 50 % of range
Address area	
Address space per module	
● Address space per module, max.	16 byte
Hardware configuration	

© Copyright Siemes

Automatic encoding	Yes
● Mechanical coding element	Yes
● Type of mechanical coding element	Type A
Selection of BaseUnit for connection variants	
● 1-wire connection	BU type A0, A1
● 2-wire connection	BU type A0, A1
● 4-wire connection	BU type A0, A1 + potential distributor module
Analog inputs	
Number of analog inputs	8; Single-ended
● For current measurement	8
permissible input current for current input (destruction limit), max.	50 mA
Cycle time (all channels), min.	1 ms; per channel
Input ranges (rated values), currents	
● 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	100 Ω; 15 bit
● -20 mA to +20 mA	Yes
— Input resistance (-20 mA to +20 mA)	100 Ω; 16 bit incl. sign
● 4 mA to 20 mA	Yes
— Input resistance (4 mA to 20 mA)	100 Ω; 15 bit
Cable length	
● shielded, max.	200 m
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
● Resolution with overrange (bit including sign), max.	16 bit
● Integration time, parameterizable	Yes
● Interference voltage suppression for interference frequency f1 in Hz	16.67 / 50 / 60 / 4 800 (16.67 / 50 / 60)
● Conversion time (per channel)	180 / 60 / 50 / 0.625 (67.5 / 22.5 / 18.75) ms
Smoothing of measured values	
● Number of smoothing levels	4
● Parameterizable	Yes
● Step: None	Yes
● Step: low	Yes; 4x smoothing
● Step: Medium	Yes; 8x smoothing
● Step: High	Yes; 16x smoothing
Encoder	
Connection of signal encoders	
● for voltage measurement	No
● for current measurement as 2-wire transducer	Yes
— Burden of 2-wire transmitter, max.	650 Ω
● for current measurement as 4-wire transducer	Yes
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.01 %
Temperature error (relative to input range), (+/-)	0.005 %/K
Crosstalk between the inputs, min.	50 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.05 %
Operational error limit in overall temperature range	
● Current, relative to input range, (+/-)	0.7 %
Basic error limit (operational limit at 25 °C)	
● Current, relative to input range, (+/-)	0.3 %
Interference voltage suppression for f = n x (f1 +/- 1 %), f1 = interference frequency	
● Series mode interference (peak value of interference < rated value of input range), min.	70 dB; With conversion time 67.5 / 22.5 / 18.75 ms: 40 dB
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
● Diagnostic alarm	Yes
● Limit value alarm	No

© Copyright Siemes

Diagnoses	
● Monitoring the supply voltage	Yes
● Wire break	Yes; at 4 to 20 mA
● Short-circuit	Yes; Sensor supply to M; module by module
● Group error	Yes
● Overflow/Underflow	Yes; module-wise
Diagnostics indication LED	
● Monitoring of the supply voltage (PWR-LED)	Yes; green LED
● Channel status display	Yes; green LED
● for channel diagnostics	No
● for module diagnostics	Yes; green/red DIAG LED
Potential separation	
Potential separation channels	
● between the channels	No
● between the channels and backplane bus	Yes
● between the channels and the power supply of the electronics	No
Isolation	
Isolation tested with	707 V DC (type test)
Security	
signed firmware update	Yes; firmware V2.0.0 or higher
safely removing data	Yes; firmware V2.0.0 or higher
data integrity	Yes; firmware V2.0.0 or higher
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-40 °C; = Tmin (incl. condensation/frost)
● horizontal installation, max.	70 °C; = Tmax
● vertical installation, min.	-40 °C; = Tmin
● vertical installation, max.	50 °C; = Tmax
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	5 000 m
● Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
● With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation
Resistance	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
— Against mechanical environmental conditions acc. to EN 60721-3-3	Yes; Class 3M8 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0)
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
— Against mechanical environmental conditions acc. to EN 60721-3-6	Yes; Class 6M4 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0)
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas

© Copyright Siemes

and control systems acc. to ANSI/ISA-71.04	concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
Conformal coating	
● Coatings for printed circuit board assemblies acc. to EN 61086	Yes; Class 2 for high reliability
● Protection against fouling acc. to EN 60664-3	Yes; Type 1 protection
● Military testing according to MIL-I-46058C, Amendment 7	Yes; Discoloration of coating possible during service life
● Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, Class A
Dimensions	
Width	15 mm
Height	73 mm
Depth	58 mm
Weights	
Weight, approx.	31 g

Classifications

	Version	Classification
eClass	16	27-24-26-01
eClass	14	27-24-26-01
eClass	12	27-24-26-01
eClass	9.1	27-24-26-01
eClass	9	27-24-26-01
eClass	8	27-24-26-01
eClass	7.1	27-24-26-01
eClass	6	27-24-26-01
ETIM	10	EC001596
ETIM	9	EC001596
ETIM	8	EC001596
ETIM	7	EC001596
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Manufacturer Declaration | China RoHS

General Product Approval	EMV	For use in hazardous locations		Maritime application
China RoHS	RCM	ATEX	IECEx	CCC-Ex	DNV

last modified: 3/10/2026

Subject to change without notice
© Copyright Siemens