SIEMENS

Data sheet 6AG1243-2AA30-7XB0



Figure similar

SIPLUS S7-1200 CM 1243-2 based on 3RK7243-2AA30-0XB0 with conformal coating, -25…+70 °C, S7-1200, CM 1243-2 communications module AS-Interface master according to AS-i specification V3.0

General technical data		
product designation		SIPLUS AS-Interface master
product type designation		CM 1243-2
protection class IP		IP20
type of electrical connection of the AS-Interface		Screw-type connection
type of voltage supply		via backplane bus
consumed current		
● from profile conductors of the AS-Interface		
— at 30 V maximum	mA	100
● from backplane bus maximum	mA	250
power loss [W]	W	2.9
insulation voltage rated value	V	500
product feature redundancy capability		No
product function suitable for AS-i Power24V		Yes
● note		All product versions
display version		
● as status display by LED		AS-i, PF, CM, CER, DIAG
type of configuration of the AS-Interface		With STEP7, command interface
Communication/ Protocol		
version of the AS-Interface specification		V 3.0
AS-Interface master profile is supported		M4 (in acc. with AS-interface specification V 3.0)
type of data transmission		S7-1200 backplane bus
number of units per CPU maximum		3
number of units per CPU maximum note		Max. 3 communication modules in total (CM /CP)
number of interfaces		
● as AS-Interface		1
● according to USB		0
protocol is supported		
● TCP/IP		No
Inputs/ Outputs		
number of inputs for AS-Interface maximum		496
number of outputs for AS-Interface maximum		496
number of AS-i devices per AS-Interface maximum		62
access to digital I/O data		via process image/peripheral addresses
access to analog I/O data		via process diagram/peripheral addresses and data record transfer
Mechanical data		
fastening method		snap-on fastening on 35 mm DIN rail

Subject to change without notice
© Copyright Siemes

module format		S7-1200 design
Ambient conditions		
ambient temperature		
● if installed on horizontal mounting rail during operation	°C	0 ... 55
● if installed on vertical mounting rail during operation	°C	-25 ... +70
installation altitude at height above sea level maximum	m	2 000
Safety related data		
explosion protection marking for intrinsic safety of related equipment		
● EEx ia		No
● EEx ib		No
explosion protection category for gas		none
explosion protection category for dust		none

Certificates/ approvals

General Product Approval

Manufacturer Declaration | China RoHS | China RoHS

General Product Approval	For use in hazardous locations

Further information

Information on the packaging
https://www.siemes.plc.com/?s=6AG1243-2AA30-7XB0

Information for data generation and storage
https://www.siemes.plc.com/?s=6AG1243-2AA30-7XB0

Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemes.plc.com/?s=6AG1243-2AA30-7XB0

Industry Mall (Online ordering system)
https://www.siemes.plc.com/?s=6AG1243-2AA30-7XB0

Cax online generator
https://www.siemes.plc.com/?s=6AG1243-2AA30-7XB0

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://www.siemes.plc.com/?s=6AG1243-2AA30-7XB0

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
https://www.siemes.plc.com/?s=6AG1243-2AA30-7XB0

last modified: 4/17/2025

© Copyright Siemes