SIEMENS

Data sheet 6AG1244-0BB12-2PA1



SIPLUS G120 CU240E-2 DP based on 6SL3244-0BB12-1PA1 with conformal coating, -20…+55 °C, Control Unit CU240E-2 DP E-type with Safety Integrated STO PROFIBUS DP 6 DI, 3 DQ, 2 AI, 2 AQ, max. 1F-DI PTC/KTY interface USB and SD/MMC interface degree of protection IP20 ambient temperature 0 to +50 °C without Power Module

General information	
Product type designation	CU240E-2 DP
based on	6SL3244-0BB12-1PA1
Product function	
● V/f control with linear/square parameterization capability	Yes
● V/f control with ECO mode linear/square	Yes
● V/f control with flux current control	Yes
● Vector control with encoder	No
● Vector control without encoder	Yes
Supply voltage	
Operating voltage from Power Module	24 V
Operating voltage from external power supply, min.	20.4 V
Operating voltage from external power supply, max.	28.8 V
Input current	
Current consumption, max.	0.5 A
Power loss	
Power loss, max.	5.5 W
Digital inputs	
Number of digital inputs	6; Optically isolated, free reference potential (own potential group), NPN/PNP-logic selectable via wiring
● With fail-safe	1; Use of 2x DI Standard
Digital outputs	
Number of digital outputs	
● As transistor	1
● As relay change-over contact	2
Analog inputs	
Number of analog inputs	2; the differential analog inputs can be configured as supplementary digital inputs
Type of analog input	Differential input
Remark	Switchable between voltage (-10 ... +10 V) and current (0/4 ... 20 mA) using a DIP switch
Input voltage with signal "0" to "1"	4 V
Input voltage with signal "1" to "0"	1.6 V
Analog outputs	
Number of analog outputs	2
Analog value generation for the inputs	
A/D resolution	10 bit
Interfaces	
Number of PROFINET interfaces	0

© Copyright Siemes

Number of RS 485 interfaces	1
Protocols	
PROFIBUS	Yes
Isolation	
Type of protective insulation	PELV according to EN 50178, safe disconnection from the mains by double/reinforced isolation
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
Certificate of suitability	CE / TÜV
Ambient conditions	
Ambient temperature during operation	
● min.	-20 °C; = Tmin
● max.	55 °C; = Tmax
● min. [°F]	-4 °F
● max. [°F]	131 °F
● Remark	A derating of 3 K/1 000 m has to be applied to the Control Units from an installation altitude of 1 000 m above sea level
Ambient temperature during storage/transportation	
● Storage, min.	-40 °C
● Storage, max.	70 °C
● Storage, min. [°F]	-40 °F
● Storage, max. [°F]	158 °F
Relative humidity	
● With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	No
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
Conformal coating	
● Coatings for printed circuit board assemblies acc. to EN 61086	Yes; Class 2 for high reliability
● Military testing according to MIL-I-46058C, Amendment 7	Yes; Discoloration of coating possible during service life
● Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, Class A
Connection method	
Type of electrical connection for signal line	
● Connectable conductor cross-section for signal line, min.	0.05 mm²
● Connectable conductor cross-section for signal line, max.	1.5 mm²
● Connectable conductor cross-section for AWG cables, min.	30
● Connectable conductor cross-section for AWG cables, max.	16
Dimensions	
Width	73 mm
Height	199 mm
Depth	46 mm

© Copyright Siemes

Weights

Weight (without packaging)	0.49 kg

Classifications

	Version	Classification
eClass	16	27-02-31-50
eClass	14	27-02-31-50
eClass	12	27-02-31-50
eClass	9.1	27-02-31-50
eClass	9	27-02-31-01
eClass	8	27-02-31-01
eClass	7.1	27-02-31-01
eClass	6	27-02-31-01
ETIM	10	EC001857
ETIM	9	EC001857
ETIM	8	EC001857
ETIM	7	EC001857
IDEA	4	5208
UNSPSC	15	39-12-22-14

Approvals / Certificates

General Product Approval

Manufacturer Declaration

China RoHS

China RoHS

General Product Approval	EMV	Functional Saftey	Test Certificates
		TUEV	TUEV

last modified: 5/29/2024

Subject to change without notice
© Copyright Siemens