SIEMENS

Data sheet 6AG1322-1HF10-2AA0



Figure similar

spare part SIPLUS S7-300 SM 322 40-pole based on 6ES7322-1HF10-0AA0 with conformal coating, -25…+60 °C, digital output isolated 8 DO (relay), 1x 40-pole, 24 V DC, 5 A or 230 V AC, 5 A, plugs with spring-loaded terminal can be used from 6ES7392-1BM01-0AA0

General information	
based on	6ES7322-1HF10-0AA0
Supply voltage	
Load voltage L+	
● Rated value (DC)	120 V
Load voltage L1	
● Rated value (AC)	230 V
Input current	
from supply voltage L+, max.	125 mA
from backplane bus 5 V DC, max.	40 mA
Power loss	
Power loss, typ.	4.2 W
Digital outputs	
Number of digital outputs	8; Relays
Short-circuit protection	No; to be provided externally
Controlling a digital input	Yes
Switching capacity of the outputs	
● on lamp load, max.	1 500 W; 230 V AC
● Low energy/fluorescent lamps with electronic control gear	10x 58 W
● Fluorescent tubes, conventionally compensated	1x 58 W
● Fluorescent tubes, uncompensated	10x 58 W
Output current	
● for signal "1" rated value	5 A
● for signal "1" minimum load current	5 mA
Parallel switching of two outputs	
● for uprating	No
● for redundant control of a load	Yes
Switching frequency	
● with resistive load, max.	2 Hz
● with inductive load, max.	0.5 Hz
● With inductive load (to IEC 60947-5-1, DC13/AC15), max.	0.5 Hz
● on lamp load, max.	2 Hz
● mechanical, max.	10 Hz
Total current of the outputs (per group)	
horizontal installation	
— up to 60 °C, max.	5 A
— up to 70 °C, max.	5 A
vertical installation	

© Copyright Siemes

— up to 40 °C, max.	5 A
Relay outputs	
● Rated supply voltage of relay coil L+ (DC)	24 V
● Contact connection (internal)	No
● Number of operating cycles, max.	300 000; 300 000 (24 V DC, at 2 A); 200 000 (120 V AC, at 3 A); 100 000 (230 V AC, at 3 A)
Switching capacity of contacts	
— with inductive load, max.	3 A; 3 A (230 V DC), 2 A (24 V AC)
— with resistive load, max.	8 A; 8 A (230 V DC), 5 A (24 V AC)
— Thermal continuous current, max.	8 A
Cable length	
● shielded, max.	1 000 m
● unshielded, max.	600 m
Interrupts/diagnostics/status information	
Alarms	No
Diagnostics function	No
Alarms	
● Diagnostic alarm	No
Diagnoses	
● Wire break	No
● short-circuit	No
● Fuse blown	No
● Missing load voltage	No
Diagnostics indication LED	
● Rated load voltage PWR (green)	No
● Fuse OK FSG (green)	No
● Status indicator digital output (green)	Yes
Potential separation	
Potential separation digital outputs	
● between the channels	Yes
● between the channels, in groups of	1
● between the channels and backplane bus	Yes; Optocoupler
Isolation	
Isolation tested with	2 000 V AC
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes; File E239877
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
Railway application	
● EN 50155	Yes; Sections 4, 5 and 12; no further agreements apply; T1, Category 1, Class A/B, EN 50155:2007 (see SIOS entry 109755985)
Ambient conditions	
Ambient temperature during operation	
● min.	-25 °C; = Tmin
● max.	60 °C
Ambient temperature during storage/transportation	
● min.	-40 °C
● max.	70 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	2 000 m
● Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m)
Relative humidity	
● With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request

© Copyright Siemes

— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on land craft, rail vehicles and special-purpose vehicles	
— to biologically active substances according to EN 60721-3-5	Yes; Class 5B2 mold, fungus and dry rot spores (with the exception of fauna); Class 5B3 on request
— to chemically active substances according to EN 60721-3-5	Yes; Class 5C3 (RH < 75 %) incl. salt spray acc. to EN 50155 (ST2); *
— to mechanically active substances according to EN 60721-3-5	Yes; Class 5S3 incl. sand, dust; *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
Connection method	
required front connector	40-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	320 g

Classifications

	Version	Classification
eClass	16	27-24-22-04
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

China RoHS | Manufacturer Declaration | Declaration of Conformity

© Copyright Siemens

General Product Approval	EMV







last modified: 5/29/2024

© Copyright Siemes