SIEMENS

Data sheet 6AG1331-7PF01-4AB0



Figure similar

spare part SIPLUS S7-300 SM 331 8 AI based on 6ES7331-7PF01-0AB0 with conformal coating, 0…+60 °C, analog input isolated, 2/3/4-wire, 8 AI, resistor, Pt100/200/1000 NI100/120/200/500/1000, CU10, characteristic curves according to GOST 16 (internal 24) bit, 50 ms, 1x 40-pole

General information	
based on	6ES7331-7PF01-0AB0
Product function	
● Isochronous mode	No
Supply voltage	
Load voltage L+	
● Rated value (DC)	24 V
● Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	240 mA
from backplane bus 5 V DC, max.	100 mA
Power loss	
Power loss, typ.	4.6 W
Analog inputs	
Number of analog inputs	8
● For resistance measurement	8
permissible input voltage for voltage input (destruction limit), max.	75 V; 35 V continuous, 75 V for max. 1 s (mark to space ratio 1:20)
Input ranges	
● Voltage	No
● Current	No
● Thermocouple	No
● Resistance thermometer	Yes
● Resistance	Yes
Input ranges (rated values), voltages	
● 0 to +10 V	No
● 1 V to 5 V	No
● 1 V to 10 V	No
● -1 V to +1 V	No
● -10 V to +10 V	No
● -2.5 V to +2.5 V	No
● -250 mV to +250 mV	No
● -5 V to +5 V	No
● -50 mV to +50 mV	No
● -500 mV to +500 mV	No
● -80 mV to +80 mV	No
Input ranges (rated values), currents	
● 0 to 20 mA	No

© Copyright Siemes

● -10 mA to +10 mA	No
● -20 mA to +20 mA	No
● -3.2 mA to +3.2 mA	No
● 4 mA to 20 mA	No
Input ranges (rated values), thermocouples	
● type B	No
● type C	No
● Type E	No
● Type J	No
● Type K	No
● Type L	No
● Type N	No
● Type R	No
● Type S	No
● Type T	No
● Type U	No
● Type TXK/TXK(L) to GOST	No
Input ranges (rated values), resistance thermometer	
● Cu 10	Yes
● Ni 100	Yes
● Ni 1000	Yes
● LG-Ni 1000	Yes
● Ni 120	Yes
● Ni 200	Yes
● Ni 500	Yes
● Pt 100	Yes
● Pt 1000	Yes
● Pt 200	Yes
● Pt 500	Yes
Input ranges (rated values), resistors	
● 0 to 150 ohms	Yes
● 0 to 300 ohms	Yes
● 0 to 600 ohms	Yes
Characteristic linearization	
● Parameterizable	Yes
— for resistance thermometer	Pt100, Pt200, Pt500, Pt1000, Ni100, Ni120, Ni200, Ni500, Ni1000, Cu10; (standard/climate)
Cable length	
● shielded, max.	200 m
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
● Resolution with overrange (bit including sign), max.	16 bit; Two's complement
● Integration time, parameterizable	Yes
● Basic conversion time (ms)	up to 4 channels: 10 ms per module, over 5 channels: 190 ms per module, 8 channels: 80 ms
● Interference voltage suppression for interference frequency f1 in Hz	400 / 60 / 50 Hz
Encoder	
Connection of signal encoders	
● for resistance measurement with two-wire connection	Yes; without resistance correction
● for resistance measurement with three-wire connection	Yes
● for resistance measurement with four-wire connection	Yes
Errors/accuracies	
Operational error limit in overall temperature range	
● Resistance, relative to input range, (+/-)	0.1 %
● Resistance thermometer, relative to input range, (+/-)	±1 K
Basic error limit (operational limit at 25 °C)	
● Resistance, relative to input range, (+/-)	0.05 %
● Resistance thermometer, relative to input range, (+/-)	±0.5 K

© Copyright Siemes

Interrupts/diagnostics/status information	
Diagnostics function	Yes; Parameterizable
Alarms	
● Diagnostic alarm	Yes; Parameterizable per group
● Limit value alarm	Yes; Parameterizable
● Hardware interrupt	Yes; Parameterizable, channels 0 to 7
Diagnoses	
● Diagnostic information readable	Yes
Diagnostics indication LED	
● Group error SF (red)	Yes
Potential separation	
Potential separation analog inputs	
● between the channels	No
● between the channels, in groups of	2
● between the channels and backplane bus	Yes
● between the channels and the power supply of the electronics	Yes
Isolation	
Isolation tested with	500 V DC
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes; File E239877
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
Railway application	
● EN 50121-4	No
● EN 50155	No
Ambient conditions	
Ambient temperature during operation	
● min.	0 °C; = Tmin
● max.	60 °C; = Tmax
Ambient temperature during storage/transportation	
● min.	-40 °C
● max.	70 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	5 000 m
● Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
● With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas

© Copyright Siemes

and control systems acc. to ANSI/ISA-71.04	concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
Connection method	
required front connector	40-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	272 g

Classifications

	Version	Classification
eClass	16	27-24-22-01
eClass	14	27-24-22-01
eClass	12	27-24-22-01
eClass	9.1	27-24-22-01
eClass	9	27-24-22-01
eClass	8	27-24-22-01
eClass	7.1	27-24-22-01
eClass	6	27-24-22-01
ETIM	10	EC001420
ETIM	9	EC001420
ETIM	8	EC001420
ETIM	7	EC001420
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Manufacturer Declaration

China RoHS

EMV

For use in hazardous locations

CCC-Ex

last modified: 5/29/2024

© Copyright Siemens