SIEMENS

Data sheet 6AG1341-1AH02-7AE0



Figure similar

spare part SIPLUS S7-300 CP 341 based on 6ES7341-1AH02-0AE0 with conformal coating, -25…+70 °C, communications processor with RS-232C interface (RS-232-C) incl. configuration package on CD-ROM

General information	
based on	6ES7341-1AH02-0AE0
Supply voltage	
Rated value (DC)	
● 24 V DC	Yes
Input current	
from supply voltage L+, max.	100 mA
from backplane bus 5 V DC, max.	70 mA
Power loss	
Power loss, typ.	1.6 W
Power loss, max.	2.4 W
Interfaces	
Interfaces/bus type	RS 232C (V.24)
Number of interfaces	1; Isolated
Transmission rate, min.	0.3 kbit/s
Transmission rate, max.	115.2 kbit/s
Point-to-point connection	
● Cable length, max.	15 m
● supported printers	Serial printers
● Connector type	9-pin sub D connector
Integrated protocol driver	
— 3964 (R)	Yes
— ASCII	Yes
— RK 512	Yes
Telegram length, max.	
— 3964 (R)	4 096 byte
— ASCII	4 096 byte
— RK 512	4 096 byte
Transmission speed, RS 232	
— with 3964 (R) protocol, max.	115.2 kbit/s
— with ASCII protocol, max.	115.2 kbit/s
— with printer driver, max.	115.2 kbit/s
— with RK 512 protocol, max.	115.2 kbit/s
Interrupts/diagnostics/status information	
Diagnostics indication LED	
● Receive RxD	Yes
● Transmit TxD	Yes
● Group error SF (red)	Yes

© Copyright Siemes

Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes; File E239877
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
Ambient conditions	
Ambient temperature during operation	
● min.	-25 °C; = Tmin
● max.	70 °C; = Tmax; 60 °C @ UL/cUL, ATEX and FM use
Ambient temperature during storage/transportation	
● min.	-40 °C
● max.	70 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	5 000 m
● Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
● With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
Software	
Block	
● FB length in RAM, max.	6 100 byte; Data communication, sending and receiving
Connection method	
Design of electrical connection for supply voltage	3 screw-type terminals: L+, M, GND
Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	300 g
Classifications	

	Version	Classification
eClass	16	27-24-22-08
eClass	14	27-24-22-08
eClass	12	27-24-22-08

© Copyright Siemes

eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	10	EC001423
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Manufacturer Declaration

China RoHS

EMV

For use in hazardous locations

CCC-Ex

last modified: 12/8/2024

Subject to change without notice
© Copyright Siemes