SIEMENS

Data sheet 6AG1343-1CX10-2XE0

product type designation	**CP 343-1 LEAN**



spare part SIPLUS NET CP 343-1 Lean based on 6GK7343-1CX10-0XE0 with conformal coating, -25…+60 °C, communications processor for connection of SIMATIC S7-300 to Industrial Ethernet via TCP/IP and UDP, multicast, send/receive with and without RFC1006, fetch/ write, S7 communication (server) PROFINET IO device integrated 2-port switch ERTEC 200, module replacement without PG, SNMP diagnostics, initialization via LAN,

product brand name	SIPLUS
Technical Product Detail Page	https://www.siemes.plc.com/?s=6AG1343-1CX10-2XE0
transfer rate	
transfer rate	
● at the 1st interface	10 ... 100 Mbit/s
interfaces	
number of interfaces / according to Industrial Ethernet	2
number of electrical connections	
● at the 1st interface / according to Industrial Ethernet	2
● for power supply	1
type of electrical connection	
● of Industrial Ethernet interface	RJ45 port
● at the 1st interface / according to Industrial Ethernet	RJ45 port
type of electrical connection	
● for power supply	2-pole plugable terminal block
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	5 V
supply voltage	24 V
supply voltage / external	24 V
supply voltage / external / at DC / rated value	24 V
relative positive tolerance / at DC / at 24 V	20 %
relative negative tolerance / at DC / at 24 V	15 %
consumed current	
● from backplane bus / at DC / at 5 V / typical	0.2 A
● from external supply voltage / at DC / at 24 V / typical	0.16 A
● from external supply voltage / at DC / at 24 V / maximum	0.2 A
power loss [W]	5.8 W
ambient conditions	
ambient temperature	
● for vertical installation / during operation	-25 ... +40 °C
● for horizontally arranged busbars / during operation	-25 ... +60 °C
● during storage	-40 ... +70 °C
● during transport	-40 ... +70 °C
installation altitude / at height above sea level / maximum	5000 m
ambient condition / relating to ambient temperature - air pressure - installation altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)

© Copyright Siemes

relative humidity	
● with condensation / according to IEC 60068-2-38 / maximum	100 %; RH including condensation/frost (no commissioning when condensation is present), horizontal installation
chemical resistance / to commercially available cooling lubricants	Yes; incl. airborne diesel and oil droplets
resistance to biologically active substances	
● conformity according to EN 60721-3-3	Yes; Class 3B2 mold and fungal spores (excluding fauna), Class 3B3 on request
● conformity according to EN 60721-3-6	Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)
resistance to chemically active substances	
● conformity according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray in accordance with EN 60068-2-52 (Severity 3). The supplied plug covers must remain in place on the unused interfaces during operation.
● conformity according to EN 60721-3-6	Yes
resistance to mechanically active substances	
● conformity according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
● conformity according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
coating / for equipped printed circuit board / according to EN 61086	Yes; Class 2 for high availability
type of coating / protection against pollution according to EN 60664-3	Yes; Protection of the type 1
type of test / of the coating / according to MIL-I-46058C	Yes; Coating discoloration during service life possible
product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, class A
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-300 single width
width	40 mm
height	125 mm
depth	120 mm
net weight	0.22 kg
fastening method	
● S7-300 rail mounting	Yes
performance data / open communication	
number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	8
data volume	
● as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum	8 Kibyte
● as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum	8 Kibyte
● as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum	2 Kibyte
number of Multicast stations	8
performance data / S7 communication	
number of possible connections / for S7 communication	
● maximum	4
service	
● of SIMATIC communication / as server	Yes
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	12
performance data / PROFINET communication / as PN IO controller	
product function / PROFINET IO controller	No
performance data / PROFINET communication / as PN IO device	
product function / PROFINET IO device	Yes
data volume	
● as user data for input variables / as PROFINET IO device / maximum	512 byte

© Copyright Siemes

● as user data for output variables / as PROFINET IO device / maximum	512 byte
● as user data for input variables / for each sub-module as PROFINET IO device	240 byte
● as user data for output variables / for each sub-module as PROFINET IO device	240 byte
● as user data for the consistency area for each sub-module	240 byte
number of submodules / per PROFINET IO-Device	32
performance data / telecontrol	
protocol / is supported	
● TCP/IP	Yes
product functions / management, configuration, engineering	
product function / MIB support	Yes
protocol / is supported	
● SNMP v1	Yes
● DCP	Yes
● LLDP	Yes
configuration software	
● required	STEP 7 V5.4 or higher / STEP 7 Professional V11 (TIA Portal) or higher
identification & maintenance function	
● I&M0 - device-specific information	Yes
● I&M1 - higher level designation/location designation	Yes
product functions / diagnostics	
product function / web-based diagnostics	Yes
product functions / switch	
product feature / switch	Yes
product function	
● switch-managed	No
● with IRT / PROFINET IO switch	No
● configuration with STEP 7	Yes
product functions / redundancy	
product function	
● ring redundancy	Yes
● redundancy manager	No
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product functions / security	
product function	
● password protection for Web applications	No
● ACL - IP-based	Yes
● ACL - IP-based for PLC/routing	No
● switch-off of non-required services	Yes
● blocking of communication via physical ports	Yes
● log file for unauthorized access	No
product functions / time	
product function / SICLOCK support	Yes
product function / pass on time synchronization	Yes
protocol / is supported	
● NTP	Yes
further information / internet links	
internet link	
● to website: Selection guide for cables and connectors	https://www.siemes.plc.com/?s=6AG1343-1CX10-2XE0
● to web page: selection aid TIA Selection Tool	https://www.siemes.plc.com/?s=6AG1343-1CX10-2XE0
● to website: Industrial communication	https://www.siemes.plc.com/?s=6AG1343-1CX10-2XE0
● to web page: SiePortal	https://www.siemes.plc.com/?s=6AG1343-1CX10-2XE0
● to website: Image database	https://www.siemes.plc.com/?s=6AG1343-1CX10-2XE0
● to website: CAx-Download-Manager	
● to website: Industry Online Support	https://www.siemes.plc.com/?s=6AG1343-1CX10-2XE0
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions

© Copyright Siemes

that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemes.plc.com/?s=6AG1343-1CX10-2XE0. (V4.7)

Approvals / Certificates

General Product Approval

Manufacturer Declaration

China RoHS

General Product Approval | EMV | For use in hazardous locations

CCC-Ex

For use in hazardous locations

last modified: 3/10/2026

© Copyright Siemes