SIEMENS

Data sheet 6AG1443-5DX05-4XE0

product type designation	**CP 443-5 Extended**
	SIPLUS NET CP 443-5 based on 6GK7443-5DX05-0XE0 with conformal coating, 0…+60 °C, communications processor extended for connection of SIMATIC S7-400 on PROFIBUS, DP, S5-compatible PG/OP and S7 communication



Figure similar

product brand name	SIPLUS
Technical Product Detail Page	https://www.siemes.plc.com/?s=6AG1443-5DX05-4XE0
transfer rate	
transfer rate	
● at the 1st interface / according to PROFIBUS	9.6 kbit/s ... 12 Mbit/s
interfaces	
number of interfaces / according to Industrial Ethernet	0
number of electrical connections	
● at the 1st interface / according to PROFIBUS	1
type of electrical connection	
● at the 1st interface / according to PROFIBUS	9-pin Sub-D socket (RS485)
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	5 V
relative symmetrical tolerance / at DC	
● at 5 V	5 %
consumed current	
● from backplane bus / at DC / at 5 V / typical	0.6 A
power loss [W]	3 W
ambient conditions	
ambient temperature	
● during operation	0 ... 60 °C
● during storage	-40 ... +70 °C
● during transport	-40 ... +70 °C
installation altitude / at height above sea level / maximum	5000 m
ambient condition / relating to ambient temperature - air pressure - installation altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
relative humidity	
● with condensation / according to IEC 60068-2-38 / maximum	100 %; RH including condensation/frost (no commissioning when condensation is present), horizontal installation
chemical resistance / to commercially available cooling lubricants	Yes; incl. airborne diesel and oil droplets
resistance to biologically active substances	
● conformity according to EN 60721-3-3	Yes; Class 3B2 mold and fungal spores (excluding fauna), Class 3B3 on request
● conformity according to EN 60721-3-6	Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)
resistance to chemically active substances	

Subject to change without notice
© Copyright Siemes

● conformity according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray in accordance with EN 60068-2-52 (Severity 3). The supplied plug covers must remain in place on the unused interfaces during operation.
● conformity according to EN 60721-3-6	Yes
resistance to mechanically active substances	
● conformity according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
● conformity according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
coating / for equipped printed circuit board / according to EN 61086	Yes; Class 2 for high availability
type of coating / protection against pollution according to EN 60664-3	Yes; Protection of the type 1
type of test / of the coating / according to MIL-I-46058C	Yes; Coating discoloration during service life possible
product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, class A
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-400 single width
width	25 mm
height	290 mm
depth	210 mm
net weight	0.65 kg
product features, product functions, product components / general	
number of units	
● per CPU / maximum	14
● note	The number of CPs that can be operated as DP masters depends on the number of CP 443-1 Advanced processors operating in the S7-400 station as PROFINET IO controllers. Up to 10 CPs can be operated in total: up to 4 as PROFINET IO controllers (CP 443-1 Advanced); up to 10 as DP masters (CP 443-5 Extended)
performance data / open communication	
number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	32
data volume	
● as user data per connection / for open communication / by means of SEND/RECEIVE blocks / maximum	240 byte
performance data / PROFIBUS DP	
service / as DP master	
● DPV1	Yes
number of DP devices	
● on DP master / operable	125
data volume	
● of the address range of the inputs / as DP master / total	4096 byte
● of the address range of the outputs / as DP master / total	4096 byte
● of the address range of the inputs / per DP device	244 byte
● of the address range of the outputs / per DP device	244 byte
performance data / S7 communication	
number of possible connections / for S7 communication	
● maximum	48
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	
● without DP / maximum	59
● with DP / maximum	54
product functions / management, configuration, engineering	
configuration software	
● required	STEP 7 V5.4 SP4 or higher / STEP 7 Professional V12 (TIA Portal) or higher
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022
product functions / routing	
number of possible connections / with data set routing / maximum	30
product functions / time	

© Copyright Siemes

product function / pass on time synchronization	Yes
protocol / is supported	
● SIMATIC time synchronization (SIMATIC Time)	Yes

further information / internet links

internet link	
● to website: Selection guide for cables and connectors	https://www.siemens.plc.com/?s=6AG1443-5DX05-4XE0
● to web page: selection aid TIA Selection Tool	https://www.siemens.plc.com/?s=6AG1443-5DX05-4XE0
● to website: Industrial communication	https://www.siemens.plc.com/?s=6AG1443-5DX05-4XE0
● to web page: SiePortal	https://www.siemens.plc.com/?s=6AG1443-5DX05-4XE0
● to website: Image database	https://www.siemens.plc.com/?s=6AG1443-5DX05-4XE0
● to website: CAx-Download-Manager	
● to website: Industry Online Support	https://www.siemens.plc.com/?s=6AG1443-5DX05-4XE0

security information

security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.plc.com/?s=6AG1443-5DX05-4XE0. (V4.7)

Approvals / Certificates

General Product Approval

Manufacturer Declaration | China RoHS | China RoHS

General Product Approval | **EMV** | **For use in hazardous locations**

CCC-Ex

For use in hazardous locations

last modified: 3/10/2026

© Copyright Siemes