SIEMENS

Data sheet 6AG4012-2CB10-0XX0

SIMATIC IPC347G (rack PC, 19", 4 U); 2x Gbit Ethernet, 1x DP, 1x VGA, 2x USB on the front, 4x USB on the rear, 2x USB internal, 2x serial, 2x PS/2, audio; no DVD +/-RW; 100/240 V industrial power supply, without power supply cable Core i7 6700 (4C/8T, 3.4 (4.0) GHz, 8 MB cache, 256 GB SSD; 4 GB DDR4; PS 350W; without operating system, drivers & documentation on USB flash drive

General information	
Product type designation	IPC347G
Installation type/mounting	
Mounting	For horizontal and vertical mounting
Design	Rack PC, 19", 4U
Supply voltage	
Type of supply voltage	100 - 240 V AC
Line frequency	
● Rated value 50 Hz	Yes
● Rated value 60 Hz	Yes
Processor	
Processor type	Core i7-6700 (4C/4T, 3.6 (4.0) GHz, 8 MB Cache)
Chipset	Intel H110
Drives	
Hard disk	HDD & SSD
Storage	
Main memory	4 / 8 / 16 GB, supports up to 32 GB
Capacity of main memory, max.	32 Gbyte
Interfaces	
serial interface	2x COM ports (RS 232, RS 422, RS 485) and 2x COM pin header
Video interfaces	
● Graphics interface	1x DisplayPort, 1x VGA
Industrial Ethernet	
● Industrial Ethernet interface	
— 100 Mbps	Yes
— 1000 Mbps	Yes
Interrupts/diagnostics/status information	
LED status display	POWER, HDD
Degree and class of protection	
IP (at the front)	IP20
IP (rear)	IP20
Ambient conditions	
Ambient temperature during operation	
● min.	5 °C
● max.	40 °C
Dimensions	
Width	430 mm
Height	176 mm
Depth	465.8 mm
Approvals / Certificates	
General Product Approval	

Miscellaneous | Manufacturer Declaration | CE EG-Konf. | UKCA | UL | Miscellaneous

Subject to change without notice
© Copyright Siemens

General Product Approval					EMV
RCM	EAC	BIS CRS	KC	China RoHS	RCM

other
IECEx

last modified: 4/2/2026

© Copyright Siemes