SIEMENS

Data sheet 6AG4131-3GG30-3AA0

SIMATIC IPC627E (Box PC), UHD Graphics onboard; DP/DVI-D; 3x Gigbit Ethernet (IE/PN); 6x USB V3.1 Gen.2; 1x serial (COM 1); RAID controller onboard; Watchdog, temperature and fan monitoring; Core i7-8700 (6C/12T, 3.2(4.6) GHz, 12 MB cache, VT-d, AMT); RAID1 2x SSD 2.5" SATA 480 GB in removable frame; 32 GB DDR4-2666 (2x16); 24 V DC industrial power supply Windows 10 Enterprise 2019 LTSC, 64-bit, MUI (en, de, fr, it, es) For Core i7; without expansion (software); without expansion (HW); 2x PCI

General information	
Product type designation	IPC627E
Installation type/mounting	
Mounting	Wall mounting, portrait mounting
Design	Box PC, built-in unit
Supply voltage	
Type of supply voltage	100/240 V AC (autorange); 24 V DC
Line frequency	
● Rated value 50 Hz	Yes
● Rated value 60 Hz	Yes
Mains buffering	
● Mains/voltage failure stored energy time	20 ms
Processor	
Processor type	Celeron G4900 (2C/2T, 3.1 GHz, 2 MB cache; VT-d); Core i3-8100 (4C/4T, 3.6 GHz, 6 MB cache, VT-d); Core i7-8700 (6C/12T, 3.2 (4.6) GHz, 12 MB cache, VT-d, AMT)
Chipset	Intel C246
Graphic	
Graphics controller	Intel UHD Graphics 630 (Core i); Intel UHD Graphics 610 (Celeron)
Drives	
Hard disk	2.5" SATA ≥ 320 GB
SSD	Yes; SSD M.2 NVMe 512 GB; SSD 2.5" SATA 480 / 960 GB; RAID1 2x SSD 2.5" SATA 480 / 960 GB in removable drive bay
Storage	
Type of memory	DDR4-2666 DIMM
Main memory	4 / 8 / 16 / 32 / 64 GB
Capacity of main memory, max.	64 Gbyte
Data areas and their retentivity	
Retentive data area (incl. timers, counters, flags), max.	512 kbyte; 128 KB can be stored in the buffer time
Hardware configuration	
Slots	
● Number of PCI slots	3; Optional
● Number of PCI slots	5; Optional
Interfaces	
Number of industrial Ethernet interfaces	3; 3x Ethernet (RJ45)
serial interface	1x COM
Video interfaces	
● Graphics interface	2x DisplayPort; 1x DVI-D
Industrial Ethernet	
● Industrial Ethernet interface	
— 100 Mbps	Yes
— 1000 Mbps	Yes
Interrupts/diagnostics/status information	
LED status display	1x power, 3x user
Integrated Functions	
Monitoring functions	

© Copyright Siemes

● Temperature monitoring	Yes
● Fan	Yes
● Monitoring function via network	Optional
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
cULus	Yes; UL 61010-2-201 Second Edition; CAN/CSA-C22.2 No. 61010-2-201 Second Edition
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
FCC	Yes
BSMI	Yes
Use in hazardous areas	
● cULus Class I Zone 2, Division 2	Yes; Optional
Marine approval	
● American Bureau of Shipping (ABS)	Yes; Only with SSD
● Bureau Veritas (BV)	Yes; Only with SSD
● Det Norske Veritas (DNV)	Yes; Only with SSD
● Korean Register of Shipping (KRS)	Yes; Only with SSD
● Lloyds Register of Shipping (LRS)	Yes; Only with SSD
● Nippon Kaiji Kyokai (Class NK)	Yes; Only with SSD
● Chinese Classification Society (CCS)	Yes; Only with SSD
Ambient conditions	
Ambient temperature during operation	
● min.	5 °C
● max.	55 °C
Ambient temperature during storage/transportation	
● min.	-20 °C
● max.	60 °C
Vibrations	
● Vibration resistance during operation acc. to IEC 60068-2-6	tested according to DIN IEC 60068-2-6: 10 Hz to 58 Hz: 0.075 mm; 58 Hz to 500 Hz 9.8 m/s² (1 g)
Operating systems	
pre-installed operating system	Windows 10 Enterprise 2016 LTSB or 2019 LTSC or 2021 LTSC 64 bit, MUI
without operating system	Yes; Optional
pre-installed operating system	
● Windows 10 Enterprise	Yes; Windows 10 Enterprise 2016 LTSB or 2019 LTSC or 2021 LTSC 64 bit, MUI
Dimensions	
Width	314 mm
Height	93 mm; For variant 5x PCI(e): 155 mm
Depth	301 mm; incl. mounting rail

Approvals / Certificates

General Product Approval

Manufacturer Declaration

inspection certificate

General Product Approval | **Maritime application**

BIS CRS

© Copyright Siemens

Maritime application					
			NK / Nippon Kaiji Kyokai	CCS (China Classification Society)	KR (Korean Register of Shipping)

other	Dangerous goods	Environment	
	Dangerous goods information	Environmental Confirmations	Environmental Confirmations

last modified: 6/10/2026

Subject to change without notice
© Copyright Siemes