SIEMENS

Data sheet 6AV7251-7RC00-0GA0

SIMATIC IPC477E PRO fully protected IP65; 19" multi-touch (1366 x 768); neutral front; for support arm (expandable, round pipe) 4 USB (back); without USB (front); Ethernet (10/100/1000 Xeon E3-1505L; 3x Gbit Ethernet (IE/PN); 16 GB; without RS 232/RS485; without PCIe; without operating system; Without replaceable mass storage; 480 GB solid-state drive SATA Without SIMATIC software 24 V DC industrial power supply

Standards, approvals, certificates	
Ecological footprint	
● environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	836 kg
— global warming potential, (during production) [CO2 eq]	143 kg
— global warming potential, (during operation) [CO2 eq]	720 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-30.2 kg

Approvals / Certificates

General Product Approval					For use in hazard-ous locations
Miscellaneous	UL	EAC	BIS CRS	China RoHS	IECEx

For use in hazardous locations			Maritime application		
Miscellaneous	IECEx	ATEX	ABS	BUREAU VERITAS	LRS

Maritime application	Dangerous goods		Environment
NK / Nippon Kaiji Ky-okai	Dangerous goods in-formation	Test Summary Report UN 38.3	EPD

last modified: 5/23/2026

Subject to change without notice
© Copyright Siemes