SIEMENS

## Data sheet 6AV7676-1AC00-0AA0

SIMATIC IPC MD-34A Desk Dock accessories; MD-34A all configurations; 1x LAN 10/100 Mbps, 2x USB 2.0; 1x RS-232; 1x VGA, DC-in 19 V side; 2x USB 2.0; use the MD-34A power supply cord for the Desk Dock




| | |
|---|---|
| **General information** | |
| Design of the programming device | Mobile computer |
| **Supply voltage** | |
| Rated value (DC) | 19 V |
| permissible range, lower limit (AC) | 100 V |
| permissible range, upper limit (AC) | 240 V |
| **Interfaces** | |
| Number of RS 232 interfaces | 1 |
| Number of USB interfaces | 4 |
| ● Type A | 4; 2* USB 2.0 in rear I/O 2* USB 2.0 in the side I/O |
| Video interfaces | |
| ● analog video signal (VGA) | Yes |
| Industrial Ethernet | |
| ● Industrial Ethernet interface | |
| — 100 Mbps | Yes; 1* 10/100 MBits/s |
| ● Wake on LAN | No |
| ● IAMT (Intel Active Management Technology) | No |
| **Standards, approvals, certificates** | |
| CE mark | Yes |
| **Ambient conditions** | |
| Ambient temperature during operation | |
| ● min. | 0 °C |
| ● max. | 45 °C |
| Ambient temperature during storage/transportation | |
| ● min. | -20 °C |
| ● max. | 60 °C |
| Relative humidity | |
| ● Operation, min. | 50 % |
| ● Operation, max. | 95 % |
| **Dimensions** | |
| Width | 292 mm |
| Height | 133 mm |
| Depth | 99 mm |
| **Weights** | |
| Weight, approx. | 770 mg |
| **Classifications** | |

| | Version | Classification |
|---|---|---|
| eClass | 16 | 27-33-02-92 |


Subject to change without notice
© Copyright Siemes

| | | |
|---|---|---|
| eClass | 14 | 27-33-02-92 |
| eClass | 12 | 27-33-02-92 |
| eClass | 9.1 | 27-33-02-92 |
| eClass | 9 | 27-33-02-92 |
| eClass | 8 | 27-24-92-03 |
| eClass | 7.1 | 27-24-92-03 |
| eClass | 6 | 27-24-92-03 |
| ETIM | 10 | EC002584 |
| ETIM | 9 | EC002584 |
| ETIM | 8 | EC002584 |
| ETIM | 7 | EC002584 |

## Approvals / Certificates

### General Product Approval

Manufacturer Declaration

China RoHS

**last modified:** 6/13/2026


Subject to change without notice
© Copyright Siemes