SIEMENS

Data sheet 6ES7132-6MD00-0BB1

Siemens EcoTech



SIMATIC ET 200SP, relay module normally open, RQ NO-MA4x120VDC..230VAC/5A ST, with manual operation, packing unit VPE 1, suitable for BU type B0 or B1, Module diagnostics

General information	
Product type designation	RQ 4x120 V DC ... 230 V AC/5 A NO MA ST
HW functional status	From FS03
Firmware version	
● FW update possible	Yes
usable BaseUnits	BU type B0, B1
Color code for module-specific color-coded label	CC40
Product function	
● I&M data	Yes; I&M0 to I&M3
● Isochronous mode	No
Engineering with	
● STEP 7 TIA Portal configurable/integrated from version	V13 SP1
● STEP 7 configurable/integrated from version	V5.5 SP3 / -
● PROFIBUS from GSD version/GSD revision	One GSD file each, Revision 3 and 5 and higher
● PROFINET from GSD version/GSD revision	GSDML V2.3
Operating mode	
● DQ	Yes
● DQ with energy-saving function	No
● PWM	No
● Oversampling	No
● MSO	No
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption, max.	100 mA; without load
Power loss	
Power loss, typ.	1.5 W
Address area	
Address space per module	
● Inputs	1 byte; + 1 byte for QI information
● Outputs	1 byte
Hardware configuration	
Automatic encoding	Yes

© Copyright Siemes

● Mechanical coding element	Yes
● Type of mechanical coding element	type C
Selection of BaseUnit for connection variants	
● 2-wire connection	BU type B1
● 3-wire connection	BU type B0
Digital outputs	
Type of digital output	Relays
Number of digital outputs	4
Current-sinking	Yes
Current-sourcing	Yes
Digital outputs, parameterizable	Yes
Short-circuit protection	No
Switching frequency	
● with resistive load, max.	2 Hz
● with inductive load (acc. to IEC 60947-5-1, DC13), max.	0.5 Hz; provide one freewheeling diode for switching frequencies higher than 0.1 Hz
● with inductive load (acc. to IEC 60947-5-1, AC15), max.	0.5 Hz
● on lamp load, max.	2 Hz
Total current of the outputs	
● Current per channel, max.	5 A
● Current per module, max.	20 A
Total current of the outputs (per module)	
horizontal installation	
— up to 50 °C, max.	20 A
— up to 60 °C, max.	16 A
vertical installation	
— up to 40 °C, max.	20 A
— up to 50 °C, max.	16 A
Relay outputs	
● Number of relay outputs	4
● Rated supply voltage of relay coil L+ (DC)	24 V
● Current consumption of relays (coil current of all relays), max.	40 mA
● external protection for relay outputs	Yes, with miniature fuse max. 6 A tripping current and quick-response tripping characteristic
● Number of operating cycles, max.	7 000 000; see additional description in the manual
Switching capacity of contacts	
— with inductive load, max.	2 A; see additional description in the manual
— with resistive load, max.	5 A; see additional description in the manual
— Thermal continuous current, max.	5 A
— Switching current, min.	100 mA; 5 V DC
— Rated switching voltage (DC)	24 V DC to 120 V DC
— Rated switching voltage (AC)	24V AC to 230V AC
Cable length	
● shielded, max.	1 000 m
● unshielded, max.	200 m
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Substitute values connectable	Yes
Alarms	
● Diagnostic alarm	Yes
Diagnoses	
● Monitoring the supply voltage	Yes
● Wire break	No
● Short-circuit	No
● Group error	Yes
Diagnostics indication LED	
● Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
● Channel status display	Yes; green LED
● for channel diagnostics	No

© Copyright Siemens

● for module diagnostics	Yes; green/red DIAG LED
Potential separation	
Potential separation channels	
● between the channels	Yes
● between the channels and backplane bus	Yes
● between the channels and the power supply of the electronics	Yes
Permissible potential difference	
between channels and backplane bus/supply voltage	240 V AC
Isolation	
Isolation tested with	2 500 V DC (type test)
tested with	
● between channels and backplane bus/supply voltage	2 500 V DC
● between backplane bus and supply voltage	707 V DC (type test)
Standards, approvals, certificates	
Suitable for safety functions	No
Ecological footprint	
● environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	25.5 kg
— global warming potential, (during production) [CO2 eq]	3.54 kg
— global warming potential, (during operation) [CO2 eq]	22.1 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.137 kg
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-30 °C
● horizontal installation, max.	60 °C
● vertical installation, min.	-30 °C
● vertical installation, max.	50 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	2 000 m; On request: Installation altitudes greater than 2 000 m
Absolute humidity	
● dew point, min.	-60 °C; suitable for dry room applications
Dimensions	
Width	20 mm
Height	73 mm
Depth	58 mm
Weights	
Weight, approx.	45 g
Classifications	

	Version	Classification
eClass	16	27-24-26-04
eClass	14	27-24-26-04
eClass	12	27-24-26-04
eClass	9.1	27-24-26-04
eClass	9	27-24-26-04
eClass	8	27-24-26-04
eClass	7.1	27-24-26-04
eClass	6	27-24-26-04
ETIM	10	EC001599
ETIM	9	EC001599
ETIM	8	EC001599
ETIM	7	EC001599
IDEA	4	3566

© Copyright Siemes

	UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval




Miscellaneous
Manufacturer Declaration




General Product Approval




China RoHS





For use in hazardous locations

Maritime application

FM








NK / Nippon Kaiji Kyokai

Maritime application

Environment





CCS (China Classification Society)
KR (Korean Register of Shipping)




last modified: 2/1/2026

© Copyright Siemens