SIEMENS

Data sheet 6ES7151-1BA02-0AB0



Figure similar

*** Spare part *** SIMATIC DP, Interface module IM151-1 High Feature f. ET200S; Transmission rate to 12 Mbit/s; data volume 244 bytes each for I/O max. 63 modules can be connected; isochronous mode Bus connection via 9-pin D-sub incl. termination module

General information	
Product type designation	IM 151-1 HF
Product function	
● Isochronous mode	Yes
Supply voltage	
Mains buffering	
● Mains/voltage failure stored energy time	20 ms
Input current	
from supply voltage 1L+, max.	200 mA
Power loss	
Power loss, typ.	3.3 W
Address area	
Addressing volume	
● Inputs	244 byte
● Outputs	244 byte
Interfaces	
Transmission procedure	RS 485
Transmission rate, max.	12 Mbit/s
Protocols	
Supports protocol for PROFINET IO	No
PROFIBUS DP	Yes
PROFIBUS DP	
Services	
— SYNC capability	Yes
— FREEZE capability	Yes
— Direct data exchange (slave-to-slave communication)	Yes
Interrupts/diagnostics/status information	
Alarms	Yes
Diagnostics function	Yes
Diagnostics indication LED	
● Bus fault BF (red)	Yes
● Group error SF (red)	Yes
● Monitoring 24 V voltage supply ON (green)	Yes
Potential separation	
between backplane bus and electronics	No
between electronic block and PROFIBUS DP	Yes
between supply voltage and electronics	No

© Copyright Siemes

Isolation	
Isolation tested with	500 V DC
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
Ambient conditions	
Ambient temperature during operation	
● min.	0 °C
● max.	60 °C
Dimensions	
Width	45 mm
Height	119.5 mm
Depth	75 mm
Weights	
Weight, approx.	150 g

Classifications

	Version	Classification
eClass	16	27-24-26-08
eClass	14	27-24-26-08
eClass	12	27-24-26-08
eClass	9.1	27-24-26-08
eClass	9	27-24-26-08
eClass	8	27-24-26-08
eClass	7.1	27-24-26-08
eClass	6	27-24-26-08
ETIM	10	EC001604
ETIM	9	EC001604
ETIM	8	EC001604
ETIM	7	EC001604
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Miscellaneous | Manufacturer Declaration | UL | RCM | EAC | China RoHS

EMV | **For use in hazardous locations**

RCM | ATEX | FM | ATEX | UL | ATEX

For use in hazardous locations | **Maritime application**

IECEx | Miscellaneous | CCC-Ex | ABS | BUREAU VERITAS | DNV

Maritime application

© Copyright Siemes



NK / Nippon Kaiji Kyokai



CCS (China Classification Society)

last modified: 7/31/2025

Subject to change without notice
© Copyright Siemes