SIEMENS

Data sheet 6ES7193-4JB00-0AA0



plug, socket, 2x2-pole, ET 200S/SP/BL/MB interface module, S7-1500 CPU, KP32F, PN-PN coupler, grid size 5.08 mm cage clamp technology, internally bridged, color-coded, scope of supply: 10 plugs

General information	
Product type designation	Connector, female, 2x2-pin
Installation type/mounting	
Wall mounting/direct mounting	Yes; can be plugged into SIMATIC HMI device
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
Interfaces	
HMI-side interface	
● Number of pins HMI-side	2; Outgoing side jumpered internally, color-coded
Device-side interface	
● Number of pins device-side	4; Female, spring-loaded terminals 0.75 mm²
Standards, approvals, certificates	
CE mark	Yes
RoHS conformity	Yes
China RoHS compliance	Yes
Ambient conditions	
Ambient temperature during storage/transportation	
● min.	-20 °C
● max.	70 °C
Mechanics/material	
Design of housing	plastic
Dimensions	
Width	10 mm
Height	22 mm
Thickness	25 mm
Scope of supply	
Delivery quantity in pieces	10
Other	
Merchandise	No
Manufacturer name	SIEMENS AG
Manufacturer's address	Gleiwitzerstraße 555, 90475 Nuremberg, Germany
Note:	For ET 200S, interface module, KP32F, PN/PN coupler
Usable in the following products	
● Product 1	6AV3688-3EH47-0AX0
● Product 2	6AV7863*
● Product 3	6AV7862-2*
Classifications	

Subject to change without notice
© Copyright Siemes

	Version	Classification
eClass	16	27-24-26-92
eClass	14	27-24-26-92
eClass	12	27-24-26-92
eClass	9.1	27-24-26-92
eClass	9	27-24-26-92
eClass	8	27-24-26-92
eClass	7.1	27-24-26-92
eClass	6	27-24-26-92
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval

Manufacturer Declaration

General Product Approval | EMV

last modified: 4/7/2025

Subject to change without notice
© Copyright Siemens