SIEMENS

## Data sheet 6ES7193-6BP00-0DA0

Siemens EcoTech

SIMATIC ET 200SP, BaseUnit BU15-P16+A0+2D, BU type A0, push-in terminals, without aux. terminals, new load group, WxH: 15x 117 mm



Figure similar

| | |
|---|---|
| **General information** | |
| Product type designation | BU type A0 |
| HW functional status | From FS06 |
| **Supply voltage** | |
| Rated value (DC) | 24 V |
| external protection for power supply lines | Yes; 24 V DC/10 A miniature circuit breaker with type B or C tripping characteristic |
| Mains filter | |
| ● integrated | Yes |
| **Current carrying capacity** | |
| For P1 and P2 bus, max. | 10 A |
| For process terminals, max. | 2 A |
| **Hardware configuration** | |
| Formation of potential groups | |
| ● New potential group | Yes |
| ● Potential group continued from the left | No |
| Slots | |
| ● Number of slots | 1; Type A0 |
| **Potential separation** | |
| between the potential groups | Yes |
| **Isolation** | |
| Isolation tested with | 707 V DC (type test) |
| **Standards, approvals, certificates** | |
| Ecological footprint | |
| ● environmental product declaration | Yes |
| Global warming potential | |
| — global warming potential, (total) [CO2 eq] | 0.873 kg |
| — global warming potential, (during production) [CO2 eq] | 0.866 kg |
| — global warming potential, (during operation) [CO2 eq] | 0 kg |
| — global warming potential, (after end of life cycle) [CO2 eq] | -0.0011 kg |
| **Ambient conditions** | |
| Ambient temperature during operation | |
| ● horizontal installation, min. | -30 °C |


Subject to change without notice
© Copyright Siemes

| | |
|---|---|
| ● horizontal installation, max. | 60 °C |
| ● vertical installation, min. | -30 °C |
| ● vertical installation, max. | 50 °C |
| Altitude during operation relating to sea level | |
| ● Installation altitude above sea level, max. | 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual |
| Absolute humidity | |
| ● dew point, min. | -60 °C; suitable for dry room applications |
| **Accessories** | |
| Color coding labels | |
| ● for process terminals | CC00 to CC09 |
| ● for AUX terminals | does not exist |
| ● for add-on terminals | does not exist |
| **Connection method** | |
| Terminals | |
| ● Terminal type | Push-in terminal |
| ● system-integrated shield connection | Yes; Optional |
| ● Conductor cross-section, min. | 0.14 mm²; AWG 26 |
| ● Conductor cross-section, max. | 2.5 mm²; AWG 14 |
| ● Number of process terminals to I/O module | 16 |
| ● Number of terminals to AUX bus | 0 |
| ● Number of add-on terminals | 0 |
| ● Number of terminals with connection to P1 and P2 bus | 2 |
| **Dimensions** | |
| Width | 15 mm |
| Height | 117 mm |
| Depth | 35 mm |
| **Weights** | |
| Weight, approx. | 40 g |

**Classifications**

| | Version | Classification |
|---|---|---|
| eClass | 16 | 27-24-26-03 |
| eClass | 14 | 27-24-26-03 |
| eClass | 12 | 27-24-26-03 |
| eClass | 9.1 | 27-24-26-03 |
| eClass | 9 | 27-24-26-03 |
| eClass | 8 | 27-24-26-03 |
| eClass | 7.1 | 27-24-26-03 |
| eClass | 6 | 27-24-26-03 |
| ETIM | 10 | EC001598 |
| ETIM | 9 | EC001598 |
| ETIM | 8 | EC001598 |
| ETIM | 7 | EC001598 |
| IDEA | 4 | 3560 |
| UNSPSC | 15 | 32-15-17-04 |

**Approvals / Certificates**

**General Product Approval**

Miscellaneous

Manufacturer Declaration

**General Product Approval**


© Copyright Siemes

RCM

EAC

China RoHS

Manufacturer Declaration

CE
EG-Konf.

UKCA

**For use in hazardous locations**

UL

CCC-Ex

FM

ATEX

Type Examination Certificate

Miscellaneous

**For use in hazardous locations**

IECEx

CCC-Ex

**Maritime application**

ABS

BUREAU VERITAS

DNV

LRS

**Maritime application**

NK / Nippon Kaiji Kyokai

RINA

RMRS

CCS (China Classification Society)

KR (Korean Register of Shipping)

**Environment**

EPD

**Environment**

Siemens EcoTech

**last modified:** 2/1/2026


Subject to change without notice
© Copyright Siemes