SIEMENS

Data sheet 6ES7193-6PA00-0AA0



SIMATIC ET 200SP, spare part Server module for ET 200SP

General information	
Product type designation	Server module
Installation type/mounting	
Mounting	Mounting rail 7.5 mm and 15 mm
Input current	
Current consumption, max.	30 mA
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-30 °C
● horizontal installation, max.	60 °C
● vertical installation, min.	-30 °C
● vertical installation, max.	50 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Absolute humidity	
● dew point, min.	-60 °C; suitable for dry room applications
Dimensions	
Width	7 mm
Height	117 mm
Depth	36 mm
Weights	
Weight, approx.	19 g
Classifications	

	Version	Classification
eClass	16	27-24-26-92
eClass	14	27-24-26-92
eClass	12	27-24-26-92
eClass	9.1	27-24-26-92
eClass	9	27-24-26-92
eClass	8	27-24-26-92
eClass	7.1	27-24-26-92
eClass	6	27-24-26-92
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584

Subject to change without notice
© Copyright Siemes

IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval





Manufacturer Declaration





General Product Approval






For use in hazardous locations



CCC-Ex
FM

For use in hazardous locations





Miscellaneous
Type Examination Certificate
CCC-Ex

Maritime application



Maritime application







NK / Nippon Kaiji Kyokai




Maritime application

CCS (China Classification Society)
KR (Korean Register of Shipping)

last modified: 2/1/2026

© Copyright Siemens