SIEMENS

Data sheet 6ES7193-6SC20-1AM0



SIMATIC ET 200SP, set for 5 shield connections, with 5 shield terminals, 5 shield supports, 5 support elements

General information	
Product type designation	Shield connection
Installation type/mounting	
Mounting	can be plugged into ET 200SP BaseUnit
Ambient conditions	
Ambient temperature during operation	
● min.	-40 °C
● max.	70 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	5 000 m
Absolute humidity	
● dew point, min.	-60 °C; suitable for dry room applications
Mechanics/material	
Material	Brass, nickel-plated
Dimensions	
Width	15 mm
Height	14 mm
Depth	80 mm
Classifications	

	Version	Classification
eClass	16	27-24-26-92
eClass	14	27-24-26-92
eClass	12	27-24-26-92
eClass	9.1	27-24-26-92
eClass	9	27-24-26-92
eClass	8	27-24-26-92
eClass	7.1	27-24-26-92
eClass	6	27-24-26-92
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584

Approvals / Certificates	
General Product Approval	

Subject to change without notice
© Copyright Siemes

Manufacturer Declaration



last modified: 2/1/2026

Subject to change without notice
© Copyright Siemes