SIEMENS

## Data sheet 6ES7321-1CH00-0AA0



Figure similar

***spare part*** SIMATIC S7-300, digital input SM 321, isolated, 16 DI, 24-48 V AC/DC with single-point grounding, 1x 40-pole

| | |
|---|---|
| **General information** | |
| Product function | |
| ● Isochronous mode | No |
| **Supply voltage** | |
| Load voltage L+ | |
| ● Rated value (DC) | 24 V |
| ● permissible range, lower limit (DC) | 24 V |
| ● permissible range, upper limit (DC) | 48 V |
| Load voltage L1 | |
| ● Rated value (AC) | 24 V |
| ● permissible range, lower limit (AC) | 24 V |
| ● permissible range, upper limit (AC) | 48 V |
| **Input current** | |
| from backplane bus 5 V DC, max. | 100 mA |
| **Power loss** | |
| Power loss, typ. | 1.5 W; at 24 V; 2,8 W at 48 V |
| **Digital inputs** | |
| Number of digital inputs | 16 |
| Input characteristic curve in accordance with IEC 61131, type 1 | Yes |
| Number of simultaneously controllable inputs | |
| horizontal installation | |
| — up to 40 °C, max. | 16 |
| — up to 60 °C, max. | 16 |
| vertical installation | |
| — up to 40 °C, max. | 16 |
| Input voltage | |
| ● Type of input voltage | AC/DC |
| ● Rated value (DC) | 24 V; DC 24 or 48 V |
| ● Rated value (AC) | 24 V; 24 V AC or 48 V AC (0 ... 63 Hz) |
| ● for signal "0" | -5V AC to +5V AC |
| ● for signal "1" | 14V AC to 60V AC |
| Input current | |
| ● for signal "0", min. | -1 mA |
| ● for signal "0", max. (permissible quiescent current) | 1 mA |
| ● for signal "1", typ. | 2.7 mA |
| Input delay (for rated value of input voltage) | |
| for standard inputs | |
| — parameterizable | No |


Subject to change without notice
© Copyright Siemes

| | |
|---|---|
| — at "0" to "1", min. | 16 ms |
| — at "0" to "1", max. | 16 ms |
| — at "1" to "0", max. | 16 ms |
| Cable length | |
| ● shielded, max. | 1 000 m |
| ● unshielded, max. | 600 m |
| **Encoder** | |
| Connectable encoders | |
| ● 2-wire sensor | Yes |
| — permissible quiescent current (2-wire sensor), max. | 1 mA |
| **Interrupts/diagnostics/status information** | |
| Alarms | No |
| Diagnostics function | No |
| Alarms | |
| ● Diagnostic alarm | No |
| ● Hardware interrupt | No |
| Diagnostics indication LED | |
| ● Group error SF (red) | No |
| ● Status indicator digital input (green) | Yes |
| **Potential separation** | |
| Potential separation digital inputs | |
| ● between the channels | Yes |
| ● between the channels, in groups of | 1 |
| ● between the channels and backplane bus | Yes; Optocoupler |
| **Isolation** | |
| Isolation tested with | 1 500 V AC |
| **Connection method** | |
| required front connector | 40-pin |
| **Dimensions** | |
| Width | 40 mm |
| Height | 125 mm |
| Depth | 120 mm |
| **Weights** | |
| Weight, approx. | 260 g |

**Classifications**

| | Version | Classification |
|---|---|---|
| eClass | 16 | 27-24-22-04 |
| eClass | 14 | 27-24-22-04 |
| eClass | 12 | 27-24-22-04 |
| eClass | 9.1 | 27-24-22-04 |
| eClass | 9 | 27-24-22-04 |
| eClass | 8 | 27-24-22-04 |
| eClass | 7.1 | 27-24-22-04 |
| eClass | 6 | 27-24-22-04 |
| ETIM | 10 | EC001419 |
| ETIM | 9 | EC001419 |
| ETIM | 8 | EC001419 |
| ETIM | 7 | EC001419 |
| IDEA | 4 | 3566 |
| UNSPSC | 15 | 32-15-17-05 |

**Approvals / Certificates**

| General Product Approval | Test Certificates | other |
|---|---|---|


© Copyright Siemes

| | | | | | |
|---|---|---|---|---|---|
| EAC | CE EG-Konf. | UK CA | Type Test Certificates/Test Report | Confirmation | 产品合格 QC PASS |

| Dangerous goods | Environment |
|---|---|
| Transport Information | Environmental Confirmations |

**last modified:** 4/7/2025


© Copyright Siemes