SIEMENS

## Data sheet 6ES7355-2SH00-0AE0



***spare part*** SIMATIC S7-300, temperature Control Unit FM 355-2S, 4 channels, step and pulse, 4 AI+8 DI+8 DO incl. multi-language configuration package, manual and Getting Started (de, en, it) on CD-ROM

| | |
|---|---|
| **Supply voltage** | |
| Load voltage L+ | |
| ● Rated value (DC) | 24 V |
| ● permissible range, lower limit (DC) | 20.4 V |
| ● permissible range, upper limit (DC) | 28.8 V |
| **Input current** | |
| from load voltage L+ (without load), max. | 270 mA; typ. 220 mA |
| from backplane bus 5 V DC, max. | 75 mA; typ. 50 mA |
| **Power loss** | |
| Power loss, typ. | 5.5 W |
| Power loss, max. | 6.9 W |
| **Digital inputs** | |
| Number of digital inputs | 8 |
| Input characteristic curve in accordance with IEC 61131, type 2 | Yes |
| Input voltage | |
| ● Rated value (DC) | 24 V |
| ● for signal "0" | -3 to +5V |
| ● for signal "1" | 13 to 30V |
| Input current | |
| ● for signal "1", typ. | 7 mA |
| Cable length | |
| ● shielded, max. | 1 000 m |
| ● unshielded, max. | 600 m |
| **Digital outputs** | |
| Number of digital outputs | 8 |
| Short-circuit protection | Yes; Electronic |
| Limitation of inductive shutdown voltage to | L+ (-1.5 V) |
| Controlling a digital input | Yes |
| Switching capacity of the outputs | |
| ● on lamp load, max. | 5 W |
| Load resistance range | |
| ● lower limit | 240 Ω |
| ● upper limit | 4 kΩ |
| Output voltage | |
| ● for signal "1", min. | L+ (-2.5 V) |
| Output current | |
| ● for signal "1" rated value | 0.1 A |
| ● for signal "1" permissible range for 0 to 60 °C, min. | 5 mA |
| ● for signal "1" permissible range for 0 to 60 °C, max. | 150 mA |


© Copyright Siemes

| | |
|---|---|
| ● for signal "0" residual current, max. | 0.5 mA |
| Parallel switching of two outputs | |
| ● for logic links | Yes |
| Switching frequency | |
| ● with resistive load, max. | 100 Hz |
| ● with inductive load, max. | 0.5 Hz |
| ● on lamp load, max. | 100 Hz |
| Total current of the outputs (per group) | |
| all mounting positions | |
| — up to 60 °C, max. | 400 mA |
| Cable length | |
| ● shielded, max. | 1 000 m |
| ● unshielded, max. | 600 m |
| **Analog inputs** | |
| Number of analog inputs | 4 |
| permissible input voltage for voltage input (destruction limit), max. | 20 V |
| permissible input current for current input (destruction limit), max. | 40 mA |
| Input ranges | |
| ● Voltage | Yes |
| ● Current | Yes |
| ● Thermocouple | Yes |
| ● Resistance thermometer | Yes |
| Input ranges (rated values), voltages | |
| ● 0 to +10 V | Yes |
| — Input resistance (0 to 10 V) | 100 kΩ |
| ● -1.75 V to +11.75 V | Yes |
| — Input resistance (-1.75 V to +11.75 V) | 100 kΩ |
| Input ranges (rated values), currents | |
| ● 0 to 20 mA | Yes |
| — Input resistance (0 to 20 mA) | 50 Ω |
| ● 0 to 23.5 mA | Yes |
| — Input resistance (0 to 23.5 mA) | 50 Ω |
| ● -3.5 mA to +23.5 mA | Yes |
| — Input resistance (-3.5 mA to +23.5 mA) | 50 Ω |
| ● 4 mA to 20 mA | Yes |
| — Input resistance (4 mA to 20 mA) | 50 Ω |
| Input ranges (rated values), thermocouples | |
| ● type B | Yes |
| — Input resistance (Type B) | 10 MΩ |
| ● Type E | Yes |
| — Input resistance (Type E) | 10 MΩ |
| ● Type J | Yes |
| — Input resistance (type J) | 10 MΩ |
| ● Type K | Yes |
| — Input resistance (Type K) | 10 MΩ |
| ● Type R | Yes |
| — Input resistance (Type R) | 10 MΩ |
| ● Type S | Yes |
| — Input resistance (Type S) | 10 MΩ |
| Input ranges (rated values), resistance thermometer | |
| ● Pt 100 | Yes |
| — Input resistance (Pt 100) | 10 MΩ |
| Thermocouple (TC) | |
| Temperature compensation | |
| — internal temperature compensation | Yes |
| — external temperature compensation with Pt100 | Yes |
| Characteristic linearization | |


© Copyright Siemes

| | |
|---|---|
| ● Parameterizable | Yes |
| — for thermocouples | Type B, E, J, K, R, S |
| — for resistance thermometer | Pt100 (standard) |
| Cable length | |
| ● shielded, max. | 200 m; 50 m at 80 mV and thermocouples |
| **Analog value generation for the inputs** | |
| Integration and conversion time/resolution per channel | |
| ● Resolution with overrange (bit including sign), max. | 14 bit |
| **Encoder** | |
| Connection of signal encoders | |
| ● for voltage measurement | Yes |
| ● for current measurement as 4-wire transducer | Yes |
| Connectable encoders | |
| ● 2-wire sensor | Yes |
| — permissible quiescent current (2-wire sensor), max. | 1.5 mA |
| **Errors/accuracies** | |
| Operational error limit in overall temperature range | |
| ● Voltage, relative to input range, (+/-) | 0.06 %; ±0.06 to ±0.7% |
| ● Current, relative to input range, (+/-) | 0.06 %; ±0.06 to ±0.7% |
| ● Resistance thermometer, relative to input range, (+/-) | 0.06 %; ±0.06 to ±0.7% |
| Basic error limit (operational limit at 25 °C) | |
| ● Voltage, relative to input range, (+/-) | 0.04 %; ±0.04 to ±0.5 % |
| ● Current, relative to input range, (+/-) | 0.04 %; ±0.04 to ±0.5 % |
| ● Resistance thermometer, relative to input range, (+/-) | 0.04 %; ±0.04 to ±0.5 % |
| **Interrupts/diagnostics/status information** | |
| Substitute values connectable | Yes; Parameterizable |
| **Integrated Functions** | |
| Control technology | |
| ● Number of closed-loop controllers | 4 |
| **Potential separation** | |
| Potential separation controller | |
| ● between the channels | No |
| ● between the channels and backplane bus | Yes; Optocoupler |
| **Isolation** | |
| Isolation tested with | 500 V DC |
| **Connection method** | |
| required front connector | 2x 20-pin |
| **Dimensions** | |
| Width | 80 mm |
| Height | 125 mm |
| Depth | 120 mm |
| **Weights** | |
| Weight, approx. | 470 g |
| **Classifications** | |

| | Version | Classification |
|---|---|---|
| eClass | 16 | 27-24-22-05 |
| eClass | 14 | 27-24-22-05 |
| eClass | 12 | 27-24-22-05 |
| eClass | 9.1 | 27-24-22-05 |
| eClass | 9 | 27-24-22-05 |
| eClass | 8 | 27-24-22-05 |
| eClass | 7.1 | 27-24-22-05 |
| eClass | 6 | 27-24-22-05 |
| ETIM | 10 | EC001422 |
| ETIM | 9 | EC001422 |
| ETIM | 8 | EC001422 |


© Copyright Siemes

| | | |
|---|---|---|
| ETIM | 7 | EC001422 |
| IDEA | 4 | 3567 |
| UNSPSC | 15 | 32-15-17-05 |

## Approvals / Certificates

| General Product Approval | | | | other | |
|---|---|---|---|---|---|
| EAC | Confirmation | CE EG-Konf. | UKCA | Confirmation | 产品合格 QC PASS |

## Environment

| | |
|---|---|
| Environmental Confirmations | Environmental Confirmations |

**last modified:** 4/7/2025


Subject to change without notice
© Copyright Siemens