SIEMENS

Data sheet 6ES7400-1JA01-0AA0



Figure similar

SIMATIC S7-400, rack UR2, central and distributed with 9 slots, 2 redundant PS can be plugged in

General information	
Product type designation	UR2
Hardware configuration	
Rack	
● Communication bus	Yes
● P bus	Yes
Slots	
● Number of slots	9
Standards, approvals, certificates	
CE mark	Yes
UKCA mark	Yes
UL approval	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
CCC	Yes
Ambient conditions	
Ambient temperature during operation	
● min.	0 °C
● max.	60 °C
Ambient temperature during storage/transportation	
● min.	0 °C
● max.	70 °C
Dimensions	
Width	257.5 mm
Height	290 mm
Depth	27.5 mm
Weights	
Weight, approx.	2.15 kg
Classifications	

	Version	Classification
eClass	16	27-24-22-03
eClass	14	27-24-22-03
eClass	12	27-24-22-03
eClass	9.1	27-24-22-03
eClass	9	27-24-22-03

Subject to change without notice
© Copyright Siemes

eClass	8	27-24-22-03
eClass	7.1	27-24-22-03
eClass	6	27-24-22-03
ETIM	10	EC000810
ETIM	9	EC000810
ETIM	8	EC000810
ETIM	7	EC000810
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvals / Certificates

General Product Approval





Manufacturer Declaration

Miscellaneous





General Product Approval



China RoHS

Miscellaneous

Manufacturer Declaration

EMV





For use in hazardous locations



FM

Declaration of Conformity





Type Examination Certificate

For use in hazardous locations



Maritime application









NK / Nippon Kaiji Kyokai

Maritime application







CCS (China Classification Society)

other

Miscellaneous

Environment



last modified: 6/7/2025

© Copyright Siemens