SIEMENS

## Data sheet 6ES7400-1TA11-0AA0

SIMATIC S7-400, rack UR1 Alu, central and distributed with 18 slots, 2 redundant PS can be plugged in



Figure similar

| | |
|---|---|
| **General information** | |
| Product type designation | UR1 |
| **Hardware configuration** | |
| Rack | |
| ● Communication bus | Yes |
| ● P bus | Yes |
| Slots | |
| ● Number of slots | 18 |
| **Standards, approvals, certificates** | |
| CE mark | Yes |
| UKCA mark | Yes |
| UL approval | Yes |
| FM approval | Yes |
| RCM (formerly C-TICK) | Yes |
| KC approval | Yes |
| EAC (formerly Gost-R) | Yes |
| CCC | Yes |
| **Ambient conditions** | |
| Ambient temperature during operation | |
| ● min. | 0 °C |
| ● max. | 60 °C |
| Ambient temperature during storage/transportation | |
| ● min. | 0 °C |
| ● max. | 70 °C |
| **Mechanics/material** | |
| rack profile material | aluminum |
| **Dimensions** | |
| Width | 482.5 mm |
| Height | 290 mm |
| Depth | 27.5 mm |
| **Weights** | |
| Weight, approx. | 3 kg |
| **Classifications** | |

| | Version | Classification |
|---|---|---|
| eClass | 16 | 27-24-22-03 |
| eClass | 14 | 27-24-22-03 |
| eClass | 12 | 27-24-22-03 |


© Copyright Siemes

| | | |
|---|---|---|
| eClass | 9.1 | 27-24-22-03 |
| eClass | 9 | 27-24-22-03 |
| eClass | 8 | 27-24-22-03 |
| eClass | 7.1 | 27-24-22-03 |
| eClass | 6 | 27-24-22-03 |
| ETIM | 10 | EC000810 |
| ETIM | 9 | EC000810 |
| ETIM | 8 | EC000810 |
| ETIM | 7 | EC000810 |
| IDEA | 4 | 3560 |
| UNSPSC | 15 | 32-15-17-04 |

## Approvals / Certificates

### General Product Approval

Manufacturer Declaration

Miscellaneous

### General Product Approval

China RoHS

Miscellaneous

Manufacturer Declaration

### EMV

### For use in hazardous locations

Declaration of Conformity

FM

### For use in hazardous locations

Type Examination Certificate

### Maritime application

### Maritime application

NK / Nippon Kaiji Kyokai

CCS (China Classification Society)

### Environment

**last modified:** 6/7/2025


© Copyright Siemens