SIEMENS

Data sheet 6ES7431-1KF00-0AB0



Figure similar

SIMATIC S7-400, analog input SM 431, isolated 8 AI, resolution 13 bit, U/IResistor

Supply voltage	
Load voltage L+	
● Rated value (DC)	not necessary
Input current	
from backplane bus 5 V DC, max.	350 mA
Power loss	
Power loss, typ.	1.8 W
Analog inputs	
Number of analog inputs	8
● For voltage/current measurement	8
● For resistance measurement	4
permissible input voltage for voltage input (destruction limit), max.	50 V
permissible input current for current input (destruction limit), max.	50 mA; 40 mA continuous
Constant measurement current for resistance-type transmitter, typ.	1.67 mA
Input ranges	
● Voltage	Yes
● Current	Yes
● Thermocouple	No
● Resistance thermometer	No
● Resistance	Yes
Input ranges (rated values), voltages	
● 1 V to 5 V	Yes
— Input resistance (1 V to 5 V)	200 kΩ
● -1 V to +1 V	Yes
— Input resistance (-1 V to +1 V)	200 kΩ
● -10 V to +10 V	Yes
— Input resistance (-10 V to +10 V)	200 kΩ
Input ranges (rated values), currents	
● -20 mA to +20 mA	Yes
— Input resistance (-20 mA to +20 mA)	80 Ω
● 4 mA to 20 mA	Yes
— Input resistance (4 mA to 20 mA)	80 Ω
Input ranges (rated values), resistors	
● 0 to 600 ohms	Yes
— Input resistance (0 to 600 ohms)	usable up to 500 ohms
Cable length	

© Copyright Siemes

● shielded, max.	200 m
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
● Resolution with overrange (bit including sign), max.	13 bit
● Integration time, parameterizable	Yes
● Basic conversion time (ms)	23 / 25 ms
● Integration time (ms)	16,7 / 20 ms
● Interference voltage suppression for interference frequency f1 in Hz	50 / 60 Hz
● Basic execution time of the module (all channels released)	200 ms; 184 / 200 ms
Encoder	
Connection of signal encoders	
● for voltage measurement	Yes; possible
● for current measurement as 2-wire transducer	Yes; with external transmitter supply
● for current measurement as 4-wire transducer	Yes
● for resistance measurement with two-wire connection	Yes; Line resistances are also measured
● for resistance measurement with three-wire connection	Yes; Line resistances are also measured
● for resistance measurement with four-wire connection	Yes
Errors/accuracies	
Temperature error (relative to input range), (+/-)	0.02 %/K; ±0.02 %/K in impedance measuring range; ±0.007 % in all other measuring ranges
Operational error limit in overall temperature range	
● Voltage, relative to input range, (+/-)	1 %; ±1.0 % at ±1 V; ±0.6 % at ±10 V; ±0.7 % at 1 to 5 V
● Current, relative to input range, (+/-)	1 %; at ±20 mA, 4 to 20 mA
● Resistance, relative to input range, (+/-)	1.25 %; 0 to 500 ohms (4-conductor measurement, in range of 600 ohms)
Basic error limit (operational limit at 25 °C)	
● Voltage, relative to input range, (+/-)	0.7 %; 0.7% at ±1 V; 0.4% at ±10 V; 0.5% at 1 to 5 V
● Current, relative to input range, (+/-)	0.7 %; at ±20 mA, 4 to 20 mA
● Resistance, relative to input range, (+/-)	0.8 %; 0 to 500 ohms (4-conductor measurement, in range of 600 ohms)
Interrupts/diagnostics/status information	
Diagnostics function	No
Potential separation	
Potential separation analog inputs	
● Potential separation analog inputs	Yes; internal/external
● between the channels	No
● between the channels and backplane bus	Yes
Isolation	
Isolation tested with	2 120 V DC between bus and analog part; 500 V DC between bus and local ground; 2 120 V DC between analog part and local ground
Dimensions	
Width	25 mm
Height	290 mm
Depth	210 mm
Weights	
Weight, approx.	500 g

Classifications

	Version	Classification
eClass	16	27-24-22-01
eClass	14	27-24-22-01
eClass	12	27-24-22-01
eClass	9.1	27-24-22-01
eClass	9	27-24-22-01
eClass	8	27-24-22-01
eClass	7.1	27-24-22-01
eClass	6	27-24-22-01
ETIM	10	EC001420
ETIM	9	EC001420

© Copyright Siemes

ETIM	8	EC001420
ETIM	7	EC001420
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

CE EG-Konf. | Miscellaneous | UKCA | UL | Metrological Approval | KC

General Product Approval

RCM | China RoHS | Miscellaneous | Manufacturer Declaration

EMV

RCM | RCM

For use in hazardous locations

ATEX | FM | CCC | IECEx | Type Examination Certificate | ATEX

Maritime application

ABS | BUREAU VERITAS | DNV | LRS | NK / Nippon Kaiji Kyokai | PRS

Maritime application

RINA | RMRS | CCS (China Classification Society)

last modified: 6/7/2025

© Copyright Siemens