SIEMENS

Data sheet 6ES7523-1BP50-0AA0



SIMATIC S7-1500 digital input/output module, DI 32x24VDC BA SNK / SRC, 32 channels in groups of 16, input delay typ. 3.2 ms input type 3 (IEC 61131), sinking/sourcing input, DQ 32XDC 24V/0.3A SNK BA; 32 channels in groups of 16; 2 A per group at 60 °C; sourcing output; 35 mm wide; cables and terminal blocks to be ordered separately as accessories

General information	
Product type designation	DI 32 x 24 V DC / DQ 32 x 24 V DC/0.3A SNK BA
HW functional status	from FS01
Firmware version	V1.0.0
● FW update possible	Yes
Product function	
● I&M data	Yes; I&M0 to I&M3
● Isochronous mode	No
● Prioritized startup	No
Engineering with	
● STEP 7 TIA Portal configurable/integrated from version	V16 with HSP 0319 / V17
● STEP 7 configurable/integrated from version	V5.5 SP3 / -
● PROFIBUS from GSD version/GSD revision	V1.0 / V5.1
● PROFINET from GSD version/GSD revision	V2.35 / -
Operating mode	
● DI	Yes
● Counter	No
● DQ	Yes
● DQ with energy-saving function	No
● PWM	No
● Cam control (switching at comparison values)	No
● Oversampling	No
● MSI	Yes
● MSO	Yes
● Integrated operating cycle counter	No
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes; Through internal protection with 4 A per group
external protection for power supply lines (recommendation)	input side: 24 V DC/4 A miniature circuit breaker with type B or C tripping characteristic; output side: 24 V DC/6 A miniature circuit breaker with type B tripping characteristic
Input current	
Current consumption, max.	45 mA; without load
Output voltage	

© Copyright Siemes

Rated value (DC)	24 V
Power	
Power consumption from the backplane bus	0.6 W
Power loss	
Power loss, typ.	4.7 W
Address area	
Address space per module	
● Inputs	4 byte
● Outputs	4 byte
Digital inputs	
Number of digital inputs	32
Digital inputs, parameterizable	No
Sourcing/sinking input	Yes
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Pulse extension	No
Edge evaluation	No
Signal change flutter	No
Flutter observation window	No
Number of simultaneously controllable inputs	
● Number of simultaneously controllable inputs	32; see additional description in the manual
Digital input functions, parameterizable	
● Gate start/stop	No
● Freely usable digital input	No
● Counter	No
● Digital input with oversampling	No
Input voltage	
● Rated value (DC)	24 V
● for signal "0"	-5 ... +5 V (reference potential is COM)
● for signal "1"	-11 ... -30 V; +11 ... +30 V (reference potential is COM)
Input current	
● for signal "1", typ.	2.7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	No
— at "0" to "1", min.	3 ms
— at "0" to "1", max.	4 ms
— at "1" to "0", min.	3 ms
— at "1" to "0", max.	4 ms
for interrupt inputs	
— Parameterizable	No
for technological functions	
— parameterizable	No
Cable length	
● shielded, max.	1 000 m
● unshielded, max.	600 m
Digital outputs	
Type of digital output	Transistor
Number of digital outputs	32
Current-sinking	Yes
Current-sourcing	No
Digital outputs, parameterizable	No
Short-circuit protection	No; external fusing necessary, max. 4 A per group, tripping characteristic type B or C
Limitation of inductive shutdown voltage to	L+ (-53 V)
Controlling a digital input	Yes
Digital output functions, parameterizable	
● Switching tripped by comparison values	No
● Freely usable digital output	No
● PWM output	No

© Copyright Siemes

● Digital output with oversampling	No
Switching capacity of the outputs	
● with resistive load, max.	0.3 A
● on lamp load, max.	5 W
Load resistance range	
● lower limit	80 Ω
● upper limit	10 kΩ
Output voltage	
● for signal "1", min.	M+ (0.5 V)
Output current	
● for signal "1" rated value	0.3 A
● for signal "1" permissible range, max.	0.3 A
● for signal "0" residual current, max.	0.5 mA
Output delay with resistive load	
● "0" to "1", max.	100 µs
● "1" to "0", max.	500 µs
Parallel switching of two outputs	
● for logic links	Yes
● for uprating	No
● for redundant control of a load	Yes
Switching frequency	
● with resistive load, max.	100 Hz
● with inductive load, max.	0.5 Hz; According to IEC 60947-5-1, DC-13
● on lamp load, max.	10 Hz
Total current of the outputs	
● Current per channel, max.	0.3 A; see additional description in the manual
● Current per group, max.	2 A; see additional description in the manual
● Current per module, max.	4 A; see additional description in the manual
Cable length	
● shielded, max.	1 000 m
● unshielded, max.	600 m
Encoder	
Connectable encoders	
● 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Interrupts/diagnostics/status information	
Diagnostics function	No
Substitute values connectable	No
Alarms	
● Diagnostic alarm	No
● Maintenance interrupt	No
● Hardware interrupt	No
Diagnoses	
● Monitoring the supply voltage	No
● Wire break	No
● Short-circuit	No
● Group error	No
Diagnostics indication LED	
● RUN LED	Yes; green LED
● ERROR LED	Yes; red LED
● MAINT LED	No
● Monitoring of the supply voltage (PWR-LED)	Yes; via SIMATIC TOP connect connection module
● Channel status display	Yes; via SIMATIC TOP connect connection module
● for channel diagnostics	No
● for module diagnostics	No
Potential separation	
Potential separation channels	
● between the channels	No
● between the channels, in groups of	16; 32 when using SIMATIC TOP connect connection module

© Copyright Siemes

● between the channels and backplane bus	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Siemens Eco Profile (SEP)	Siemens EcoTech
Suitable for safety-related tripping of standard modules	No
Ecological footprint	
● environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	18.9 kg
— global warming potential, (during production) [CO2 eq]	12.1 kg
— global warming potential, (during operation) [CO2 eq]	7.66 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-1.02 kg
Security	
signed firmware update	No
safely removing data	No
data integrity	No
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-30 °C
● horizontal installation, max.	60 °C
● vertical installation, min.	-30 °C
● vertical installation, max.	40 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	5 000 m
Absolute humidity	
● dew point, min.	-60 °C; suitable for dry room applications
Dimensions	
Width	35 mm
Height	147 mm
Depth	129 mm
Weights	
Weight, approx.	250 g
Other	
Note:	Please order cable and connection modules separately

Classifications

	Version	Classification
eClass	16	27-24-22-04
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

© Copyright Siemes

Miscellaneous | Manufacturer Declaration

General Product Approval

China RoHS | Manufacturer Declaration

For use in hazardous locations

CCC-Ex

For use in hazardous locations

Type Examination Certificate | Miscellaneous | CCC-Ex

Maritime application

Maritime application

NK / Nippon Kaiji Kyokai | CCS (China Classification Society)

Maritime application

KR (Korean Register of Shipping)

Environment

last modified: 5/7/2026

© Copyright Siemens