SIEMENS

Data sheet 7KM2200-2EA00-1JB1

Siemens EcoTech

SENTRON 7KM measuring device PAC2200 CLP, L-L: 400 V, L-N: 230 V, x/1 A & x/5 A DIN rail instrument, 6 MW, 3-phase, LAN interface, Modbus TCP, LC display, MID approval, screw terminal, with internal power supply, apparent / active / reactive energy, certified load profile memory measurement and calibration regulation-compliant acc. to PTB-A 50.7



Model	
product brand name	SENTRON
product designation	Energy counter
product quality calibrated	Yes
type of measured value detection load profile	Yes
type of signal	S0
design of the energy counter	Solid-state
design of the pulse output	Electrical
General technical data	
type of the power supply network	three-wire/four-wire
operating voltage	
● between L and L minimum	3 V
● between L and L maximum	480 V
● between N and L minimum	3 V
● between N and L maximum	276 V
Protection class	
protection class IP	IP40
Main circuit	
operating frequency rated value	
● minimum	45 Hz
● maximum	65 Hz
operational current rated value	5 A
Suitability	
suitability for use	Import/export
Product details	
special product feature	MID + CLP
Product function	
product function	apparent/active/reactive energy
product function	
● backstop	Yes
● blocking code	Yes
Display and operation	
design of the display	LCD
display version	digital
Communication	
protocol is supported	Modbus TCP

© Copyright Siemens

Measuring inputs	
measurable supply voltage	
● between (PE)N and L at AC maximum rated value	230 V
● between the line conductors at AC maximum rated value	400 V
Number	
number of characters that can be displayed	12
Mechanical Design	
number of modular width units	6
fastening method	DIN rail device
Net Weight	428 g

Approvals Certificates

Environment				General Product Approval	
Environmental Confirmations	Environmental Confirmations	EPD	Siemens EcoTech	EAC	Confirmation

General Product Approval	other				
CE EG-Konf.	Miscellaneous	Type Examination Certificate	Miscellaneous	Confirmation	产品合格 QC PASS

Further information

Information on the packaging
https://www.siemes.plc.com/?s=7KM2200-2EA00-1JB1

Information for data generation and storage
https://www.siemes.plc.com/?s=7KM2200-2EA00-1JB1

Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemes.plc.com/?s=7KM2200-2EA00-1JB1

Industry Mall (Online ordering system)
https://www.siemes.plc.com/?s=7KM2200-2EA00-1JB1

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://www.siemes.plc.com/?s=7KM2200-2EA00-1JB1


Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.siemes.plc.com/?s=7KM2200-2EA00-1JB1


CAx-Online-Generator
https://www.siemes.plc.com/?s=7KM2200-2EA00-1JB1

Tender specifications
https://www.siemes.plc.com/?s=7KM2200-2EA00-1JB1

Characteristic curves
https://www.siemes.plc.com/?s=7KM2200-2EA00-1JB1 <mmp_prod_noCOMP="HAUPT"></mmp_prod__no>

© Copyright Siemes





© Copyright Siemes



last modified: 4/8/2025

© Copyright Siemes

© Copyright Siemes